

User Guide

- [About the add-on](#)
- [Getting started](#)
 - [Configuration process overview](#)
 - [Configuring the data model](#)
 - [Creating a Drive](#)
 - [Linking a Drive and data model field](#)
- [Uploading and attaching assets](#)
- [Previewing assets](#)
- [Configuring asset filters](#)
- [Managing digital assets](#)
 - [Management overview](#)
 - [Editing asset information](#)
 - [Tags and tag clouds](#)
 - [Managing digital asset versions](#)
 - [Additional configuration options](#)
 - [Finding and removing unused assets](#)
 - [Enabling asset management from perspectives](#)
- [Configuring an external Drive](#)
- [Disabling automatic asset to PDF conversion](#)
- [Known limitations](#)

About the add-on

- [Concepts overview](#)
 - [Asset storage in Drives](#)
 - [Digital asset components](#)

- [How this guide is organized](#)

Concepts overview

The TIBCO EBX® Digital Asset Manager Add-on allows you to manage digital asset storage, classification, and versioning. Once you've created a storage location, you can use the add-on to upload assets and enrich them with metadata.

Note:

You can also use the add-on's API to connect to a third-party digital asset management system. This allows you to use the third-party tool for management purposes, but still link assets to TIBCO EBX® data model fields.

The asset governance process can include adding descriptive metadata to assets, creating versions, deactivating/deleting and backing up and restoring assets. The add-on allows you to perform these tasks from simple-to-navigate screens. See [Managing digital assets](#) for more information.

Asset storage in Drives

The EBX® Digital Asset Manager Add-on uses *Drives* as physical storage locations for assets. You can use Drives as part of asset governance by creating one for asset types, assets from different sources or, any other organizational requirement. For information on creating a, and uploading assets into a Drive, see [Getting started with the add-on](#).

Digital asset components

A *Digital asset component (D.A.C.)* links a storage location to a data model field configured to use the add-on. You can then attach assets from the storage location to the field. For example, a data model table containing product information could have a field containing assets that show one or more views of the product.

How this guide is organized

This guide contains the following sections:

SECTION	CONTENTS
Getting started	This section covers initial add-on configuration. Most of the steps in this section require administrative privileges.
Uploading and attaching assets	This chapter describes how to upload assets to a Drive and attach them to a data model field. Add-on configuration must be complete prior to performing these tasks.
Previewing assets	This chapter describes behavior when previewing assets.
Configuring asset filters	This chapter outlines the different types of filters the add-on offers.
Managing digital assets	Digital asset governance can include managing basic asset information, tags, metadata and versions—all topics covered in this section. Additionally, this section discusses how to create a backup of, and restore assets.

Getting started

- [Configuration process overview](#)
- [Configuring the data model](#)
- [Creating a Drive](#)
- [Linking a Drive and data model field](#)


Configuration process overview

Assets uploaded using the add-on can benefit from its management capabilities. In order to upload, store and link assets with a data model, you must complete the configuration tasks below:

- Add a media field to a data model using the **mediaType** data type. For detailed steps to complete this task, see [Configuring the data model](#).
- Create an asset storage location, or *Drive*. For detailed steps to complete this task, see [Creating a Drive](#).

- Use a *Digital asset component (D.A.C.)* to link the media field and Drive. For detailed steps to complete this task, see [Linking a Drive and data model field](#).

The following map summarizes the tasks required to complete this process:




Configuring the data model

- [Configuration task map](#)
- [Steps to complete Task 1](#)

Configuration task map

The following map shows where you are in the add-on configuration process:



The following section outlines the steps to complete Task 1: Configuring the data model.


See also:

- [Creating a Drive](#)
- [Linking a Drive and data model field](#)
- [Configuration process overview](#)

Steps to complete Task 1

To attach a digital asset to a record, you must add a field to the data model. This field's data type must be set to **mediaType**. The following steps describe how to accomplish this:

1. Locate and open an existing, or create a new data model to which you want to add asset management capabilities.
2. In the **Navigation** pane, open *Configuration > Included data models* and click the + icon to add a data model.
3. Select the **Packaged in module** option and in the **Model properties** group, choose **ebx-addon-dama** for the **Module name** and select **/WEB-INF/ebx/schema/media-type.xsd** for the **Path in module** field.



4. After saving and closing, create a field using the **mediaType** data type in the desired table by selecting **Create child** from the table's services menu and using the following options:
 - Enter a name and optionally a label and description.
 - For the **Kind of element**, select **Group**.
 - Select **Reuse an existing type**.
 - Select **Included data models** as the **Data type** and choose **Media type** from the drop-down menu.

Add an element

Configure the new element

Name *

views

Label and description

English (United States)

Area Views

French (France)

Kind of element

☐ Field
 ☒ Group
 ☐ Association

☒ Reuse an existing type

Data type *

☐ Current data model
 ☒ Included data models

Media type

- Use the group's **Minimum/Maximum number of values** properties to specify the number of assets that users can attach to this field.

Attention:

If you configure options for this field's **Default views and tools**, it can prevent users from accessing asset management functionality.

- After clicking **Create**, you can publish the data model and, if needed, create a dataset.

See also:


- [Creating a Drive](#)
- [Linking a Drive and data model field](#)
- [Configuration process overview](#)

Creating a Drive

- [Configuration task map](#)
- [Steps to complete Task 2](#)
- [Troubleshooting Drive error messages](#)

Configuration task map

The following map shows where you are in the add-on configuration process:



The following section outlines the steps to complete Task 2: Creating a Drive.

See also:

- [Linking a Drive and data model field](#)
- [Configuring the data model](#)
- [Configuration process overview](#)

Steps to complete Task 2

A Drive specifies an asset storage location and options related to acceptable file size and storage limitations. The following example points to a location on the local machine, however the API also allows you to point to a cloud storage location. For more information, see the *Java API* documentation.

To create a Drive:

1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Drive* and open the **Drive** table. This table stores asset storage configuration information.
2. Create a new *Drive* configuration. When filling required fields, you can hover your mouse over the property and click the ? icon to view online help, or you can refer to the [Drive group](#) section in this guide. The following image highlights some configuration options.

Drive id * 25CD7EBC-CA09-4B26-AC84-D6FEFE93A667

Label and description * English (United States)
Landscapes
Drive for landscape images of travel destinations.

French (France)

Drive type * File system

Physical root path * D:\ADD-ONS\DAM\Landscapes Drive Sets the asset physical storage location

User permission * 1. Profile * [all profiles]
Allow to view digital asset of other user * ☒ Yes ☐ No
Maximum allowed file size * 52 (MB)

Specifies Drive-level permissions

Max usable space * 1,024 (MB) Determines the max amount of physical disk space this Drive can use for asset storage.

Physical used space 117.1 (MB)

Physical free space 906.9 (MB)

Image configuration Standard Image Configuration You can create a custom image configuration to set limits on the physical size (width/height) of uploaded images.

Restrict file upload ☒ Yes ☐ No

Encrypt files * No

Save Save and close Revert Close

Troubleshooting Drive error messages

The following table provides troubleshooting tips for *Drive* configuration error messages.

MESSAGE	CAUSE
You path is a file; not a folder	The path specified in the Physical root path field points to a file when it should point to a folder.

MESSAGE	CAUSE
You do not have write permission in this folder	The add-on does not have sufficient system permission to manage assets in the specified location. You may need a system administrator to raise permission levels, or use a different storage location.
This folder is not empty	You will see this message if the storage location you choose already contains files. When creating a new Drive, the storage location should be empty to avoid potential duplication of an asset's unique identifier.
Cannot create folder using this path	If the folder you specify doesn't exist, the add-on checks whether it can create the folder using the specified path. This message displays when it cannot create the folder automatically.
Comment	Displays comments applied to this asset version.
Current version	Indicates whether this version is considered the current version.
Digital asset	The digital asset of which this is a version.

See also:

- [Linking a Drive and data model field](#)
- [Configuring the data model](#)
- [Configuration process overview](#)


Linking a Drive and data model field

- [Configuration task map](#)
- [Steps to complete Task 3](#)

- [Enabling thumbnail display in tables](#)

Configuration task map

The following map shows where you are in the add-on configuration process:



The following section outlines the steps to complete Task 3: Linking a Drive and field.

See also:

- [Creating a Drive](#)
- [Configuring the data model](#)
- [Configuration process overview](#)

Steps to complete Task 3

To complete the final configuration task you link the data model field and Drive created in Tasks 1 and 2, respectively.

The following steps show how to link the media field you created in the data model with the Drive (storage location):

1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > D.A.C* and open the **Digital asset component** table and create a new record.
2. Fill the required fields, save and close. It is important to note that by default no restrictions apply to the types of files users can upload. If you want to exclude certain file types, you can enable the **Restrict file upload** option and select acceptable types in **Supported extensions** field. The add-on includes a set of default image extensions. If you want to allow other file types, you can create them in the **File extension** table located in the **Reference data** domain. Additionally, you can use the **Blacklisted extensions** field to manually exclude available file types.

Additionally, the final required property, **Tag cloud**, isn't available to edit until you've saved the initial configuration.

The following image highlights D.A.C. functionality:

The screenshot shows the configuration interface for a 'Drive' field. The 'Drive' field is highlighted with a red box. Below it, the 'User permission' section is visible. The 'Image configuration' section includes a dropdown for 'Default image configuration'. The 'Data model' and 'Field path' fields are highlighted with a red box. The 'Custom filter' field is empty. The 'Restrict file upload' section has radio buttons for 'Yes' and 'No', with 'No' selected. The 'Blacklisted Extensions' section shows '[not defined]'. The 'Display configuration' section has a dropdown for '[Mosaic] Default mosaic configuration'. The 'Table view configuration' section has a dropdown for '[Table] myConfig'. The 'Editor configuration' section has a dropdown for '[Mosaic] Default mosaic configuration'. The 'Tag cloud' section has a dropdown for 'Actions' with options 'Label and description' and 'Landscapes'. A red arrow points from the 'Drive' field to the 'Data model' and 'Field path' fields. Another red arrow points from the 'Tag cloud' section to the 'Display configuration' field. A red text box explains the purpose of the 'Tag cloud' section.

Link the physical storage location ('Drive' field) to the Media-type field in the data model.

Determine how assets display after users attach them to the data model field ('Display configuration'), whether the asset thumbnails display in the tabular views, and how they display in the 'Editor'.

Enabling thumbnail display in tables

You can specify that an asset's thumbnail displays when viewing a table. You can also specify the thumbnail display size to fit your needs.

Thumbnail display behaves as follows:

- When no assets are attached, the field is left blank.

- If multiple assets are attached, the first thumbnail displays. Or if multiple types of assets are attached, the first asset whose type supports thumbnails displays.
- If the asset type does not support thumbnails, the type's icon displays. When no icon is specified for the asset type, the default icon displays.

To enable table display of thumbnails:

1. If one does not already exist, create a view configuration and set the **View mode** to **Table view**. For instructions on creating a view configuration, see [Specifying the view mode](#).
2. Open the D.A.C. associated with the data model field that you want to display thumbnails.
3. Use the **Table view configuration** drop-down menu to select the desired view configuration.
4. Save and close. The following image shows an example thumbnail display:

Location

+ Actions ▾

☰	id ^	Country Code		State		City	Destination Type	Views of Area
☐	1	us	↗	CO	↗	Lake City	Mountains	
☐	2	us	↗	CO	↗	Silverton	Mountain	

See also:

- [Creating a Drive](#)
- [Configuring the data model](#)
- [Configuration process overview](#)

Uploading and attaching assets

- [Overview](#)

- Setting the upload mode
- Using quick upload mode
- Using standard upload mode
 - Upload and automatically attach assets
 - Upload and attach using the Editor
 - Upload assets via administrative access
 - Attaching existing assets to a field
- Performing a bulk upload

Overview

The add-on provides standard and quick-upload functionality. Administrators can use permission settings to determine this behavior. See [Setting the upload mode](#) for more information. Even when quick-upload is available, users can still use the **Editor** to upload and attach assets. See the following sections for more information:

- [Using quick upload mode](#)
- [Using standard upload mode](#)

Setting the upload mode

Administrators can specify which upload mode users can access. If you enable quick-upload, users will not see notification of duplicate assets, or errors indicating upload of invalid assets. For instance, if a user attempts to upload a file that does not meet conditions specified in D.A.C. settings, the file displays in the field with a red border and will not be attached to the field when saving.

To change the upload mode:

1. In the add-on's administrative area, navigate to and open the D.A.C. on which you want to adjust settings.
2. Open the appropriate user permission group and set the **Allow to quick upload and attach** property to the appropriate setting. Save and close.

Using quick upload mode

Use the following steps to upload and automatically attach an asset to a field:

1. Create a new, or open an existing record in the dataset containing the **media type** field to which you want to attach an asset.
2. Click the **Upload** button that displays in the **media type** field. Note: You cannot use the **Upload** option when the maximum number of assets are already attached to the field.

The screenshot shows a form titled 'Actions' with a dropdown arrow. Below the title, there's a section with fields: 'id' (value 2), 'Country Code' (value 'us'), 'State' (value 'CO'), 'City' (value 'Silverton'), 'Destination Type' (value 'Mountain'), and 'Views of Area' (value '[not defined]'). Below the 'Views of Area' field, there are two buttons: 'Edit' and 'Upload'. The 'Upload' button is highlighted with a mouse cursor, and a tooltip box appears below it containing the text 'Upload new digital asset(s)'.

3. In the pop-up window that displays, you can browse to select the files to upload and attach to the field. Once the add-on finishes attaching assets, you can edit their information. See [Management overview](#) for more information. Also, note that the quick-upload option displays no errors, or warnings during the upload process. However, if you've attempted to attach an assets that violates requirements for this field, it displays with a red outline indicating an error and it will not be attached to the field when saving. You can mouse over the asset to see information pertaining to the error.
4. After assets have been attached to the field, be sure to save before exiting.

Using standard upload mode

The following topics describe how to upload assets and attach them to a data model field:

- [Upload and automatically attach assets](#)
- [Upload and attach using the Editor](#)

- Upload assets via administrative access
- Attaching existing assets to a field

Attention:

The field and Drive must be properly configured before uploading and attaching assets. See [Linking a Drive and data model field](#) for more information.

Upload and automatically attach assets

If the Drive linked with a field doesn't contain the desired asset, use the following steps to upload and automatically attach an asset to a field:


1. Create a new, or open an existing record in the dataset containing the **media type** field to which you want to attach an asset.
2. Click the **Upload** button that displays in the **media type** field. Note: You cannot use the **Upload** option when the maximum number of assets are already attached to the field.

The screenshot shows a data entry form with the following fields and values:

- id**: 2 (with a red key icon)
- Country Code**: us
- State**: CO
- City**: Silverton
- Destination Type**: Mountain
- Views of Area**: [not defined]

Below the 'Views of Area' field, there are two buttons: 'Edit' (with a link icon) and 'Upload' (with a cloud upload icon). A mouse cursor is clicking the 'Upload' button, and a tooltip appears below it with the text 'Upload new digital asset(s)'.


3. In the pop-up window that displays, you can drag and drop, or browse to select the files to upload and attach to the field. The following image highlights features in the upload screen. Once the add-on finishes attaching assets, you can edit their information. See [Management overview](#) for more information.



Upload and attach using the Editor

The following steps describe how to upload an asset and attach it to a field using the **Editor**:

1. Create a new, or open an existing record in the dataset containing the **media type** field to which you want to attach an asset.
2. Click the **Edit** button that displays in the **media type** field to open the editor.
3. In the **Digital assets** pane click the **Upload** icon.



4. In the pop-up window that displays, you can drag and drop, or browse to select the files to upload. If you've dropped files into the upload window and want to browse to select additional files, just click the large plus thumbnail. The upload window also allows you to add tags which the add-on applies to each asset in this upload. When adding tags, you can select from existing, or create new tags by adding text and clicking the **Enter** key.
5. Click **Attach and upload**. Note that you have the additional option here of selecting **Upload** to upload assets to the Drive without attaching them to the field. Once assets have uploaded, you can select them to perform additional actions. The [Management overview](#) section covers related topics in more detail.

Upload assets via administrative access

If you have administrative privileges, you can use perform the following steps to upload an asset:

1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Digital asset* and from the **Digital asset** table's **Actions** menu and select **Upload a new digital asset**.
2. Browse to select the desired file.
3. You can create a label, description, version name, comments and tags. When adding tags, you can select from existing, or create new tags by adding text and pressing the **Enter** key.
4. Use the **Drive** drop-down list to indicate the Drive to which you want to add this asset.
5. Click **Upload**. After the process completes, the upload window refreshes and you can repeat these steps to upload additional assets.

Once you've uploaded assets, you can manage information such as label, description, state, tags and other metadata. The section, [Management overview](#), covers the asset management topic in detail.

Attaching existing assets to a field

If you have previous used the add-on to upload files to a Drive, you can quickly attach them to the field by:


1. Clicking **Edit** to open the **Editor**.

The screenshot shows a web interface titled 'Actions' with a dropdown arrow. Below the title is a form with the following fields:

- id**: 2 (with a red key icon)
- Country Code**: us (with a dropdown arrow and a small square icon to the right)
- State**: CO (with a dropdown arrow and a small square icon to the right)
- City**: Silverton
- Destination Type**: Mountain
- Views of Area**: [not defined]

Below the 'Views of Area' field, there are two buttons: 'Edit' (with a small square icon) and 'Upload' (with a small square icon). A hand cursor is pointing at the 'Edit' button, and a tooltip labeled 'Open Editor' is visible below it.


2. To attach an asset to a field, simply mark its checkbox. Select **Attachments** to show thumbnails of any assets attached to the field. When viewing the attached assets, you can detach all assets by selecting **Clear**. You can also download individual assets from the attachment view.



Performing a bulk upload

If you have administrative privileges, you can perform a bulk upload of assets contained in a ZIP file by:


1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Digital asset* and selecting the **Digital asset** table.
2. Open the **Actions** menu and select the **Import from a ZIP file** service.
3. Browse to select the desired file, and specify the upload location using the **Drive** drop-down list.
4. After clicking **Import**, the add-on keeps you apprised of its progress and displays a result page upon successful completion.
5. From the **Result** page's **Actions** menu (shown below), you can export a report of the results, or select multiple records to compare. Also, if the import fails, you can download a copy of the log file.




Previewing assets

For supported file types, the add-on opens a preview when you click an asset's thumbnail. If you select:


- an image: the add-on displays a full-size view and you can click to zoom.



- a video: the add-on automatically plays the video and enables basic playback controls.



- a document: the add-on loads the document for viewing. From the preview, you can access standard viewer features such as zoom, navigation, and search.



[Management overview](#) describes additional options available when previewing an asset from the **Editor**. The following table provides additional information pertaining to asset previews:

ASSET TYPE	NOTES
MP4	Currently, the add-on supports previewing and thumbnail generation for videos with the H.264 codec and AAC, or MP3 audio format.
PDF	The add-on does not support: • Text search for older PDFs that use JPEG2000, or JBIG formats. • Previewing files larger than 5MB.
Documents (DOC, DOCX, PPT, PPTX)	The add-on performs some conversion to display document previews. Certain style elements may display differently in the preview. If the add-on cannot create a preview, an error message displays and it allows you to download the asset. When viewing PPT or PPTX previews, text is not selectable and the search function is disabled.

Configuring asset filters

- [Overview](#)
- [Filtering records containing assets](#)
- [Adding a custom filter](#)

Overview

The add-on includes the following types of filters that administrators can configure:

- Filters can apply to tables and display records based on the presence of attached digital assets. Once configured, users can filter records using the EBX® table filter. For more information, see [Filtering records containing assets](#).
- A Java class can implement a programmatic filter that only allows users to view assets that meet certain criteria. Once a developer implements the class, an administrator can include it as part of a D.A.C. configuration. The filter is essentially transparent to users as the add-on automatically applies it when they view assets. For more information, see [Adding a custom filter](#).

Filtering records containing assets

Administrators can activate a filter that allows users to display records based on the presence of attached assets. To enable filtering:

1. Open the desired model in the DMA.
2. Navigate to *Configuration > Add-ons* and create a new record.
3. In the **Name** field, select **Digital Asset Manager**.
4. Save, close, and publish the data model.

Users can access filter functionality via the EBX® table filter. The filter's **TIBCO EBX® Digital Asset Manager Add-on search** group displays all fields in the current table configured to accept asset attachments. For each field specify a value of:

- **is null** to show records without attachments in this field.
- **is not null** to show records with attachments in this field.

1 - 2 of 2 ▾

View ▾

▾ Search

Add a criterion ▾

Apply Actions ▾

▸ Text search

▸ Validation search ☐

▾ TIBCO EBX™ Digital Asset Manager Add-on search ☐

Views of Area

is not null ▾

Documents


is null ▾

Apply

Adding a custom filter

A custom filter implemented in a Java class can provide fine-grained control over what users can view in the add-on's **Editor**. See the API documentation for information on the interface and methods required for this type of filter. Once the class has been created, configuration only requires that you include the filter class in a D.A.C. configuration. The process is outlined below:

1. Open the desired record in the **Digital asset component** table.
2. In the **Custom filter** field, enter the fully qualified name of the Java class that implements the filter.



- After saving and closing filter, the add-on applies filter functionality. The assets displayed for users in the **Editor** will be based on their permissions and the filter.

Managing digital assets

- [Management overview](#)
- [Editing asset information](#)
- [Tags and tag clouds](#)
- [Managing digital asset versions](#)
- [Additional configuration options](#)
- [Finding and removing unused assets](#)
- [Enabling asset management from perspectives](#)

Management overview

Overview of digital asset management

The add-on makes it quick and easy to find the specific digital asset you need with sophisticated searching, sorting, and information editing capabilities. In addition to options available to administrators, users can launch the following activities from the **Editor**:

- Upload new assets.
- Attach assets to a data model field.
- Use criteria to sort and filter assets.

- Select assets to view their details.
- Download, share, deactivate and delete assets.
- Open assets to apply tags, edit versions and apply metadata.

To access the **Editor**:

- Navigate to and open a data model record containing a field attached to a Drive.
- As shown below, click the **Edit** button.

The screenshot displays a web-based editor interface. At the top, there is a header bar with the text 'Actions' and a dropdown arrow. Below this, the main content area shows a form for editing a data model record. The form includes several fields: 'id' with a value of '2', 'Country Code' with a value of 'us', 'State' with a value of 'CO', 'City' with a value of 'Silverton', and 'Destination Type' with a value of 'Mountain'. The 'Views of Area' field is currently set to '[not defined]'. Below the 'Views of Area' field, there are two buttons: 'Edit' and 'Upload'. The 'Edit' button is highlighted with a mouse cursor, and a tooltip box appears next to it containing the text 'Open Editor'.

The following image highlights the main **Editor** areas:


Location : 2 > Digital Asset Manager - Editor ?


The breadcrumb above shows the current Table : Record

Select all
Upload

↓
Creation date
▼

Filter
Attachments 3


mountains3.jpg


mountains1.jpg


lake1.png


Hiking Guide.pdf


chimneyPeak1.jpg


backcountry.pdf


aspensFall1.png


mountains4.jpg

Selecting all assets attaches all assets to the current field. Select Upload to upload additional assets to the current Drive.


Set the sort order to ascending or descending and use the drop-down menu to specify the sort criteria.

Use the filter and attachments panes to locate assets and view assets attached to the current field, respectively.


As shown below, you can use the filter to locate assets. The upper portion of the filter allows you to enter keywords and performs a search on the asset's label, description, and physical name. You can also use a combination of asset creation and last update dates. The lower half of the filter pane includes options to filter assets by file extension, asset type, and tags.

Note:

In order to use the options in the **Search** group, the TIBCO EBX® Information Search Add-on must be activated and have a valid license.



You can use the editor's **Attachments** pane to display and manage assets attached to the current field:



When you select an asset in the **Editor**, an enlarged view displays. From this view you can use the icons in the top-right corner to:

- Download the selected asset. A window displays and allows you to choose the download location.
- Open the **Edit digital asset** view. From this view you can edit basic asset information, tags, versions, and metadata.
- Deactivate the asset. After deactivating an asset, only administrators can re-activate it. A deactivated asset no longer displays in the **Editor**. To re-activate the asset: Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Digital asset*. In the **Digital asset** table, double-click the asset to activate. Use the **State** drop-down list to update the asset, save, and close.
- Permanently delete the asset. When you permanently delete an asset, the add-on physically deletes it from the Drive.

- Share via email. Opens your email client with the selected asset attached to a new email.


Administrators can perform the same actions mentioned above. Additionally, they can use the add-on's administrative tools to backup/restore assets. The following sections describe how to:

- Edit an asset's basic information. See [Editing asset information](#).
- Create *Tag clouds* and *tags*, and apply them to assets. See [Tags and tag clouds](#).
- Create new versions of an asset and choose the asset considered the current version. See [Managing digital asset versions](#).
- Create metadata categories and apply them to assets, backup and restore assets, configure additional Drive options, and set user permissions. See [Additional configuration options](#).

Editing asset information

To edit an uploaded asset's general information, tags, metadata, and manage versions:


- As shown below, in the mediaType field, users can hover their mouse over an asset and select the information icon. If the record is read-only, its information displays, but actions aren't permitted.



The screenshot displays a user interface for managing digital assets. At the top, there is a grey bar with the text "Actions" and a downward arrow. Below this, the "id" field shows a red lock icon and the number "2". The form contains several input fields: "Country Code" with the value "lus", "State" with "CO", "City" with "Silverton", and "Destination Type" with "Mountain". Each of these fields has a small "x" icon and a dropdown arrow on the right, along with an external link icon. Below the form, there are two buttons: "Edit" (with an external link icon) and "Upload" (with an upload icon). At the bottom, there are three media thumbnails. The first is a video player showing a snowy mountain scene with a play button overlay and the filename "winterActivities.mp4". The second is a landscape photo of mountains with the filename "mountains4.jpg". The third is a photo of autumn foliage on a mountain slope with the filename "aspensFall1.png". A hand cursor is hovering over the third thumbnail, and a small "Information" tooltip is visible next to it.

- If an asset is available to a user in the **Editor**, they can select it to show an expanded view of the asset and click the **Edit** icon in the top-right of the screen. Depending on their permissions, they can perform actions to edit the asset.

- From **TIBCO EBX® Digital Asset Manager Add-on**, administrators can select **Manage digital assets** from the **Actions** menu. This view allows you to switch between Drives to edit any asset. Once you've located it, click the desired asset and in the **Details** pane, click the **Edit** icon above the image.



The following three tabs display in the **Edit digital asset** window:

- The **Information** tab allows you to view and edit the asset's label, description, state and tag information. You can only edit the asset's state if you have sufficient permissions. The following section, [Tags and tag clouds](#), describes these features in more detail.

Location : 1 > Digital Asset Manager - Edit digital asset

Information Version management Metadata

Physical name aspensFall1.png

Label and description * ▾ English (United States)
 aspensFall1.png

▸ French (France)

Creation date 09/08/2018 07:05:57

Last update date 09/08/2018 07:09:22

Digital asset type Image file type

File extension .PNG extension

State Activated



aspensFall1.png

Tags

mountain views x mountains x
 outdoor activities x Fall colors x

Manage associated tags.

- The **Version management** tab allows you to create new asset versions, edit the version name and comment attributes, delete asset versions, download versions, and select the current version. The [Managing digital asset versions](#) section covers these topics.

Location : 1 > Digital Asset Manager - Editor > Digital Asset Manager - Edit digital asset

Information **Version management** Metadata

New version ▾

File * aspens_Fall.png Select a file to upload as the new version.
The file extension must be the same as the digital asset's extension.

Version name Optionally, provide a name and comments.

Comment

Current version ☒ Specify whether the new asset is the current version and whether to update the label shown in the Editor.

Update label ☒

Digital asset versions

	Physical name	Version name	Comment	Current version	
	aspensFall1.png	High Resolution		☒	  
	aspensFall1.png	Low Resolution		☐	  

Set an existing version as the current version. Use the icons to edit attributes, download a copy of, or remove a version.

- The **Metadata** tab allows you to add a metadata category and value to an asset. See [Creating metadata categories](#) for more information.

Tags and tag clouds

- [Working with tags](#)
 - [Creating tags and applying them to assets](#)
- [Using tag clouds](#)

Working with tags

Tags provide descriptive metadata about assets. By creating tags based on relevant keywords that accurately define and describe assets, you enable filters and searches to retrieve the best results. To ensure consistency and accuracy, it's a good practice to double-check all asset metadata against an expected outcome.

A *tag cloud* facilitates grouping of related tags. A single tag can belong to multiple clouds. Administrators can make one or more tag clouds available to each D.A.C.

As described in the following section, you can create tags dynamically when uploading assets, or predefine tags to apply to assets at anytime.

Creating tags and applying them to assets

You can create tags in the following ways:

- When uploading an asset, you can enter a new, or select an existing tag. If you enter a new tag, the add-on automatically adds it to the asset and stores the new tag for later use. The add-on stores these tags in the tag clouds associated with this field through the D.A.C.
- If you have access to EBX® administrative features, you can navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Classification* and use the **Tag** and **Tag cloud** tables for creation. These tags will be available to users when uploading or editing an asset.

In addition to applying tags when uploading an asset, you can add tags when:

- Editing an asset:
 - Click a field's **Edit** button and select the desired asset.
 - Click the **Edit** icon to display the **Edit digital asset** screen.
 - From the **Information** tab, you can add, or remove tags. Just be sure to save your changes and refresh the asset when finished.
- Managing assets as an administrator. While under *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on*, open the **Actions** menu and select **Manage digital assets**. Select the desired asset and click the **Edit** icon to add, or remove tags.

Using tag clouds

If you have administrative privileges, you can create tag clouds and manage which tags are included in each cloud. The following steps describe the process:

1. In the **TIBCO EBX® Digital Asset Manager Add-on** administration area, navigate to *Classification > Tag cloud*.
2. Click the '+' icon to create a new *tag cloud* and provide a label and description.
3. After saving, you can add tags to this cloud by creating new, or using the **Actions** menu to associate existing tags with this cloud.

You can open any tag cloud and use its **Actions** menu to:

- Associate existing tags with this cloud.
- Delete tags from the system.
- Remove tags from the cloud.
- Duplicate tags for modification (tags must be unique)
- Move tags from this cloud to a different cloud.

Managing digital asset versions

Keeping versions of digital assets allows you to re-purpose versions, or revert to an older version if needed. Even though multiple asset versions may exist, only versions designated as the current version display in the **Mosaic** view and **Editor**.

Note:

You can attach duplicate files to the same field. When the add-on sees that the asset is a duplicate, a screen displays that allows you to preview the asset and choose whether to continue, or cancel.

To create a new version of an asset or change the current version:

1. Select an asset in the **Editor**, or in the **Manage digital assets** view.
2. Click the **Edit** icon to open the **Edit digital asset** screen.
3. Select the **Version management** tab. (If you do not need to upload a new file and are only switching to a different version, tick the radio button in the **Current version** column of the desired asset, and skip to step 7).
4. Browse to upload a new file. The uploaded file must have the same file extension as the original asset.
5. Optionally, add a **Version name**, **Comment** and select the **Current version** checkbox to automatically make this the current version. If you designate this asset as the current version, you can also enable the **Update label** option. This option updates the asset's label shown in the **Editor** to the current version's file name.

Location : 1 > Digital Asset Manager - Editor > Digital Asset Manager - Edit digital asset

Information **Version management** Metadata

New version ▾

File * aspens_Fall.png Select a file to upload as the new version.
The file extension must be the same as the digital asset's extension.

Version name Optionally, provide a name and comments.

Comment

Current version ☒ Specify whether the new asset is the current version and whether to update the label shown in the Editor.

Update label ☒

Set an existing version as the current version. Use the icons to edit attributes, download a copy of, or remove a version.

Digital asset versions

	Physical name	Version name	Comment	Current version	
	aspensFall1.png	High Resolution		☒	  
	aspensFall1.png	Low Resolution		☐	  

- Click **Create new version**. The add-on automatically applies any existing tags and metadata to the new version.
- Save and close to exit.

Additional configuration options

- [Creating metadata categories](#)
- [Backing up and restoring](#)
- [Allocating Drive disk space](#)
- [Limiting image size](#)
- [Specifying the view mode](#)
- [Whitelisting and blacklisting file formats](#)
 - [Adding new file extensions](#)
- [Setting user permissions](#)

Creating metadata categories

In addition to tags, the add-on allows you to create your own categories of metadata to enrich assets. After applying metadata categories to assets, you can further describe the assets by adding metadata values. To perform these tasks:


1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Reference data > Metadata nature* and create a new record to define a category of metadata.
2. Open an asset by selecting it in the **Manage digital assets** or **Editor** view and clicking the **Edit** icon.
3. Select the **Metadata** tab and add a new value. While in this tab, you can also edit and remove existing metadata. Be sure to save and refresh after completing your changes.

Backing up and restoring

The add-on allows you to take a single action to create a backup of all the assets it manages. When you restore the files, you'll have to enter new paths for Drives included in the backup.

To create a backup:

1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on*.
2. From the *Actions* menu > *Services* group, select **Backup**.
3. Enter a name for the zip file and click **Backup**.



Drive	Original location	Zip file name
[ON] Icon drive	C:\Users\csste\AppData\Local\Temp\ebx.platform.modules\ebx-addon-dama\icon	\driveFileFolders\[ON] Icon drive.zip
Landscapes	H:\ADDON Docs\Data\DAM Drives\DAM 1\Landscapes	\driveFileFolders\F2FCC41D-714F-40DD-8C36-CFA3F486114F.zip

4. After the process completes, you can select **Download** to save a copy of the backup file.

To restore assets:

5. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on*.
6. From the *Actions* menu > *Services* group, select **Restore**.
7. Click **Choose file** to navigate to the backup file's location.
8. After selecting the file click **Next**.

9. A table listing all backed up Drives displays. Enter new paths, and click the **Restore** checkbox for Drives you want to restore. An important note: *If you choose not to restore specific Drives, they will no longer be available.*
10. Click **Restore**.

Allocating Drive disk space

When you create a Drive configuration, you point to a system folder to use as the *Drive's physical location*. You can specify how much space you want to allocate to the Drive with the **Max usable space** property. Once asset storage reaches this threshold, you can no longer upload assets to this *Drive*, unless you physically delete assets to make room.

Limiting image size

You can use an image configuration to limit the physical size (width/height) of images. Once you've created a configuration, you can add it to any Drive, or D.A.C. The configuration used by a D.A.C. cannot allow for larger images than that used by the Drive.

Specifying the view mode

A view configuration determines how assets display when attached to a data model field.

Administrators can create configurations and use them in D.A.C.s. To create a view configuration:

1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > D.A.C. > View configuration*.
2. When you open an existing, or create a new record you can choose from the following options:
 - **Mosaic view:** Displays a tiled view of the assets. When you select this option, you'll be able to set the number of assets that display in rows and columns. You can also choose whether the view scrolls vertically, or horizontally to display additional assets.
 - **List view:** Displays assets in vertical list.
 - **Table view:** Enables display asset thumbnails when viewing a table. Use the available options to set the thumbnail size.
3. Decide whether assets display as their associated icons, or as thumbnails. When you choose:
 - To display icons, the assets display with their associated icon (if one exists).
 - To display thumbnails, you can set the thumbnail size and whether users can select an asset to expand it.

4. Choose whether quick action icons always display, or only display when users mouse over an assets thumbnail.

The following list of sample images show the outcomes of using the options mentioned above.

- List view using thumbnails:

Location : 2

Actions ▼

id

🔑

2

Country Code

✕ ▼

↗

State

✕ ▼

↗

City

Destination Type

Views of Area

↗ Edit

📁 Upload

▷

backcountry.pdf

🗑

▷


txticon.png

🗑

▼

winterActivities.mp4

🗑



▷

mountains4.jpg

🗑

▷

aspensFall1.png

🗑

- List view using icons:

39

Location : 2

Actions ▼

id
2

Country Code
us

State
CO

City
Silverton

Destination Type
Mountain

Views of Area
Edit
Upload

backcountry.pdf
i

txticon.png
i

winterActivities.mp4
i

mountains4.jpg
i

aspensFall1.png
i

Use the quick-access icons to view/edit asset information, import a new version, or delete the asset.

When an asset does not have an associated icon, a default icon displays.

- Mosaic view with thumbnails:

Location : 2

Actions ▾

id  2

Country Code  ▾ 

State  ▾ 


City

Destination Type

Views of Area  Edit  Upload


backcountry.pdf


txticon.png


winterActivities.mp4

- Mosaic view with icons:

Location : 2

Actions ▾

id  2

Country Code  ▾ 

State  ▾ 

City

Destination Type

Views of Area  Edit  Upload

 backcountry.pdf   

 txticon.png   

 winterActiviti...   

 mountains4.jpg   

 aspensFall1.png   

Whitelisting and blacklisting file formats

By default, the add-on allows upload of all file types. However, you may want to allow a set of file formats and block others, whitelist and blacklist respectively. The add-on allows you to add to a set of predefined file extensions. At the Drive level, you can restrict asset upload to only these file extensions. Alternatively, you could manually enter file extensions to blacklist. The D.A.C. level inherits permissions specified at the Drive level. However, you can override these settings. For example, you may have two different D.A.C.s linked to the same Drive. You could change permissions in the D.A.C.s so that only one of them can upload PDF files.

The following two settings are located in *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on* in the **Drive** and **Digital asset component** tables:

- When enabled, the **Restrict file upload** option in a Drive record restricts asset upload to only the asset file types listed in the *Reference data > File extension* table. When enabled in a D.A.C. record, you can further refine restrictions by selecting options in the **Supported extensions** field. If you would like to include additional file extensions in the **Supported extensions** list, see the [Adding new file extensions](#) section below.
- The **Blacklisted extensions** option only displays when the **Restrict file upload** option is disabled. This field allows you to manually enter file extensions to exclude from a Drive or D.A.C. You can use commas, semi-colons, periods, or whitespace to separate a list of extensions to blacklist. For example: `exe` , `bat` , `msi` , etc.

Adding new file extensions

To enable upload and management of additional file formats:

Note:

The following steps require administrative privileges.

1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Reference data > File extension*.
2. Create a new record and fill in the following fields:
 - **Business code:** A user friendly name for this file extension.
 - **Filename extension:** Enter the filename suffix used to identify this file type.

- **Digital asset type:** Choose an asset type from the drop-down list. This list populates with options from the **Digital asset type** table. You can create types in the table, or click **+** **Create** in the drop-down list to create a new type.
- **Icon** → *Select*, or upload an icon used to identify this file extension type. The add-on stores all icons in the **Icon drive**.

3. Save and close.

Setting user permissions

If you have administrative access, you can set user permissions. Drives and D.A.C.s apply permission settings to user profiles and grant/restrict viewing, uploading, downloading, versioning and deleting. With the ability to apply permissions at two levels (*Drive/D.A.C.*), you can fine-tune asset management.

As an example, you may want allow a user to upload assets to a Drive. However, you may not want this same user to upload, attach, or edit any assets attached to a particular field. To accomplish this, you can grant appropriate access for the Drive and restrict access with the *D.A.C.*

Note:

The add-on supports EBX® restriction policy functionality. For more in-depth information on restriction policies, see the *EBX® User Guide and Reference Guide*.

Finding and removing unused assets

The add-on provides functionality to locate and remove assets not attached to a field—an effective way to tidy-up the **Digital asset** table. As described below, administrators use a two part process to identify unused assets and select assets for removal:

1. Navigate to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Digital asset*

and select the **Digital asset** table.
2. From the table's **Actions** menu, select **Identify unused assets**. After analysis, the add-on displays only assets not attached to a field.
3. Select any assets you wish to remove and from the table's **Actions** menu, select **Permanently Delete (Physically delete)**. Press **OK** in the warning dialog to remove all selected assets.

Enabling asset management from perspectives

Administrators can attach the **Manage digital asset** service to EBX® perspectives. This service allows full control over all assets contained in a Drive. See the EBX® product documentation for more information on creating perspectives and how they work.

To add add-on functionality to a perspective:

1. Select **Manage digital assets** from the **Action** menu.

The screenshot shows a configuration window for the '[ebx-addon-dama] Manage digital assets' action. The window has a title bar with a close button. Below the title bar, there is a section for 'Input parameters' which contains four fields: 'Service key' with the value 'ebx-addon-dama@manage_asset_uiservice', 'Dataspace' with the value 'Reference', 'Dataset' with the value 'travel', and 'Drive' with the value '25CD7EBC-CA09-4B26-AC84-D6FEFE93A667'. Below the input parameters, there is a 'Selection on close' dropdown menu set to '[not defined]' with a share icon to its right. At the bottom of the window, there are four buttons: 'Save' (highlighted in blue), 'Save and close', 'Revert', and 'Close'.

2. Use the required **Dataspace** and **Dataset** fields to specify the location of the media type fields.
3. Enter one or more Drive id's—which can be found in the add-on's **Drive** table—in the **Input parameters** group **Drive** field. When entering multiple Drives, separate the entries using a semicolon. If you leave this field blank, the perspective will be able to access any Drive associated with the specified dataset.

Configuring an external Drive

The add-on allows administrators to create a Drive that connects to an externally managed asset storage location. For example, you could connect to a cloud storage location. This allows externally managed assets to be attached to EBX® data model fields.

A developer must programatically implement connection details and any third-party requirements using the add-on's API. For details and examples, see [Connecting to alternative storage locations](#). Once necessary implementation steps are complete, you can create a Drive that connects to external storage by:

1. Navigating to *Administration > User interface > TIBCO EBX® Digital Asset Manager Add-on > Drive* and open the **Drive** table. This table stores asset storage configuration information.
2. Creating a new *Drive* configuration. When filling required fields, you can hover your mouse over the property and click the ? icon to view online help, or you can refer to the [Drive group](#) section in this guide. The following image highlights some configuration options for an external Drive.

Cloud storage location

Services ▾

Drive id * BD4B220E-FAD7-4EAE-A303-D64AB745E74D

Label and description * ▾ English (United States)

Cloud storage location

This Drive connects to an externally managed storage location.

▸ French (France)

Drive type * External management ↗

External management class * [redacted].ExternalGoogleManagerDefinition ⚙

User permission * 1 ▾

Profile * Mary Manager (manager) ▾

Restriction policy * ☐ Yes ☒ No

Allow to upload new asset * ☒ Yes ☐ No

Allow to upload new version * [not supported]

Allow to change current version * [not supported]

Allow to share and download * ☒ Yes ☐ No

Allow to delete * ☒ Yes ☐ No

+

Save Save and close Revert Close

Note that the ability to upload to an externally managed storage location might be disabled programmatically.

Specifies the Java class that defines the external storage management requirements.

3. After saving and closing, you can link the Drive to a data model field using a Digital Asset Component (D.A.C.). For instructions, please see [Configuring the data model](#) and [Linking a Drive and data model field](#).

Disabling automatic asset to PDF conversion

By default, the add-on automatically converts digital assets that are Microsoft Office files to PDFs. Under certain conditions this process can significantly delay EBX® start up times. In this case, you might want to disable this behavior.

Note:

This property and behavior only apply to versions of the add-on compatible with TIBCO EBX® version 5.9.x.

To disable the automatic conversion of assets to PDFs:

1. If it is running, stop your EBX® repository.
2. Add the `ebx.addon.dama.convert.officeFiles.to.pdf` property to your `ebx.properties` file and set it to `false`.
3. Start your EBX® repository.

Known limitations

- Searching the contents of a file is not supported.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- Document previews cannot display Vietnamese text.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.

- Thumbnails of some uploaded SVG files do not display correctly.

Developer Guide

- [REST service operations](#)
- [Alternative storage locations](#)
 - [Connecting to alternative storage locations](#)
 - [Example Implementation](#)
- [Java API](#)

Alternative storage locations

- [Connecting to alternative storage locations](#)
- [Example Implementation](#)

Connecting to alternative storage locations

- [Overview](#)
- [High-level flow](#)
- [Implementing and registering a class and definition](#)

Overview

The add-on's API allows you to access alternative asset storage locations. An "alternative" storage location could be one which requires credentials and a third-party API to access. For example, assets might be stored in the cloud on Google Drive or AWS. Alternatively, you may already use a third-party tool to manage digital assets but, you want to enable data model access to these assets. Since these types of locations and use cases require management outside of EBX®, we refer to these as *externally managed storage locations*.

The headings below outline high-level implementation steps. See [Example Implementation](#) for an example implementation.

High-level flow

Several steps are required to implement access to an externally managed storage location. Those in a developer role perform most steps; as noted below, EBX® administrators complete others:

- Implement the following:
 - A class that provides add-on functionality for external storage locations. This class can also specify asset tags and search functionality.
 - A definition of the class that implements the add-on's API. EBX® must register this definition class on repository startup or from a user-run service.
 - Any classes required by third-party tools. For example, helper classes that contain connection credential and error handling information.
- Ensure that any required libraries are deployed in the same location as your `ebx.jar` file. This would include any JAR files containing your classes that implement the add-on's API. See the EBX® *Development Guide* for more information on deployment requirements.
- Steps an EBX® administrator must complete in the UI:
 - If required, run the service that registers the external storage management class.
 - Create an add-on Drive and configure it to use external storage. Ensure proper settings for user permissions.
 - Create a D.A.C. to link the data model field and Drive. Ensure proper settings for user permissions.

For instructions, see [Configuring an external Drive](#).

Implementing and registering a class and definition

As shown below, the class you write to specify Drive options for an externally managed location must implement the `ExternalManager` interface. The methods in this interface enable operations on assets stored in an external location.

```
import com.orchestranetworks.addon.dama.ext.exception.*;

import com.orchestranetworks.addon.dama.ext.resource.*;

import com.orchestranetworks.addon.dama.externalmanagement.*;

import com.orchestranetworks.addon.dama.externalmanagement.bean.*;

import com.orchestranetworks.addon.dama.externalmanagement.request.*;

import com.orchestranetworks.addon.dama.externalmanagement.response.*;
```

```
public class ExternalStorageDrive implements ExternalManager
{
    // TODO populate with required methods.
}
```

The below definition class which extends the add-on's `ExternalManagerDefinition` can be used to register your external management class. Note that in this class you can also determine whether users can upload assets to the external storage location from the add-on's **Editor**.

```
import com.orchestranetworks.addon.dama.externalmanagement.*;

public final class ExternalStorageDriveDefinition extends
ExternalManagerDefinition
{
    // Creates a new ExternalManager based on your implementation

    public ExternalManager getExternalManager()
    {
        return new ExternalStorageDrive();
    }

    // Determines whether upload to the external storage location is
    enabled

    public boolean allowUpload()
    {
        return true;
    }
}
```

```

    }

}

```

To make your external storage location implementation available as an option in the UI, it must be registered. You can register the external storage management upon EBX® startup, or by implementing a service. For more information on module and service registration, see the EBX® documentation. To register the external storage manager, add the following code to your registration servlet or service dispatcher:

```
ExternalManagerCatalog.add(new ExternalStorageDriveDefinition());
```

Example Implementation

- [Overview](#)
- [Sample external manager class](#)
 - [Class implementation](#)
 - [Search filter implementation](#)
 - [Asset creation](#)
 - [Asset deletion](#)
 - [Asset retrieval](#)
 - [Asset tags](#)
- [Sample definition class](#)
- [Registering your manager class](#)
- [Including third-party resources](#)

Overview

This section provides a sample configuration by connecting to a Google Drive. Note these requirements are specific to Google Drive at the time of publishing and your requirements will vary depending on how you plan to implement the API.

Sample external manager class

As shown below, you can begin with a manager class that implements the `ExternalManager` interface. The sample includes search functionality, asset display, and other features. Keep in mind that although you can code most add-on features including download, upload and delete, administrators can still define permissions on these actions when creating the Drive and D.A.C in the UI.

Attention:

The samples below have several references to a helper class (not shown) that has been defined to meet requirements specific to making Google Drive API calls. The contents of your helper class will depend on implementation requirements.

The sections below provide the following samples:

- [Class implementation](#)
- [Search filter implementation](#)
- [Asset creation](#)
- [Asset deletion](#)
- [Asset retrieval](#)
- [Asset tags](#)

Class implementation

```
import java.io.*;

import java.math.*;

import java.net.*;

import java.util.*;

import javax.activation.*;
```

```

import com.onwbp.base.text.bean.*;

import com.orchestranetworks.addon.dama.*;

import com.orchestranetworks.addon.dama.common.*;

import com.orchestranetworks.addon.dama.ext.bean.*;

import com.orchestranetworks.addon.dama.ext.exception.*;

import com.orchestranetworks.addon.dama.ext.exception.DAMException;

import com.orchestranetworks.addon.dama.ext.resource.*;

import com.orchestranetworks.addon.dama.externalmanagement.*;

import com.orchestranetworks.addon.dama.externalmanagement.bean.*;

import com.orchestranetworks.addon.dama.externalmanagement.request.*;

import com.orchestranetworks.addon.dama.externalmanagement.response.*;

import com.orchestranetworks.addon.dama.models.*;

import com.orchestranetworks.addon.utils.*;

/**
 *
 */

public class ExternalGoogleManager implements ExternalManager
{

    //Instance variable to access the helper class for the Google Drive

    private Drive googleDrive;

    public ExternalGoogleManager()

```

```

    {

        try

        {

            this.googleDrive =
GoogleDriveAPIHelper.getInstance().getDriveService();

        }

        catch (Exception ex)

        {

            throw new RuntimeException(ex);

        }

    }

}

//Sample method used to pass asset URL information to other methods

private String getUrl(String externalId, String fileName, String
extension, boolean isDownload)

throws UnsupportedOperationException

{

    //The network location where EBX is running

    String host = "localhost:8080";

    String providerLink = "http://" + host

        + "</your module name>/<your service dispatcher>?service=<your
service name>";

```

```

        StringBuilder urlDownload = new StringBuilder(providerLink);

urlDownload.append("&external_id=").append(URLEncoder.encode(externalId,
"UTF-8"));

        urlDownload.append("&fileName=")

                .append(URLEncoder.encode(this.getFileName(fileName,
extension), "UTF-8"));

        urlDownload.append("&extension=").append(extension);

        if (isDownload)

        {

urlDownload.append("&download=").append(Boolean.TRUE.toString());

        }

        return urlDownload.toString();

    }

    private LabelDescription getLabelDescription(String name, List<Locale>
locales)

    {

        if (AddonStringUtils.isEmpty(name))

        {

            name = DAMConstants.EMPTY_STRING;

        }

    }

```

```

        List<LabelDescriptionForLocale> labelDescriptionForLocales = new
        ArrayList<>();

        for (Locale locale : locales)

        {

            LabelDescriptionForLocale labelDesLocale = new
            LabelDescriptionForLocale();

            labelDesLocale.setLocale(locale);

            labelDesLocale.setLabel(name);

            labelDesLocale.setDescription(name);

            labelDescriptionForLocales.add(labelDesLocale);

        }

        LabelDescription labelDescription = new LabelDescription();

        labelDescription.setLocalizedDocumentations(labelDescriptionForLocales);

        return labelDescription;

    }

}

```

Search filter implementation

```

public ExternalSearchAssetsResult searchAssets(ExternalSearchRequest
searchRequest)

{

```



```

ExternalSearchAssetsResult result = new ExternalSearchAssetsResult();

SearchFilter searchFilter = searchRequest.getSearchFilter();

String keyword = (searchFilter == null) ? DAMConstants.EMPTY_STRING
    : searchFilter.getKeyword();

try
{
    FileList fileList =
this.googleDrive.files().list().setFields("*").execute();

    List<File> allFiles = fileList.GetFiles();

    List<File> filteredFiles = new ArrayList<>();

    for (File file : allFiles)
    {
        if (AddonStringUtils.isEmpty(keyword))
        {
            filteredFiles.add(file);
        }
        else
        {
            if (file.getName().contains(keyword)
                || file.getOriginalFilename().contains(keyword))
            {

```

```

        filteredFiles.add(file);

    }

}

int size = filteredFiles.size();

int pageIndex = (searchRequest.getPageIndex() < 1) ? 1 :
searchRequest.getPageIndex();

int pageSize = (searchRequest.getPageSize() < 10) ? 10 :
searchRequest.getPageSize();

int startIndex = (pageIndex - 1) * pageSize;

int endIndex = startIndex + pageSize - 1;

if (endIndex > size - 1)

{

    endIndex = size - 1;

}

List<ExternalDigitalAsset> externalAssets = new ArrayList<>();

for (int i = startIndex; i <= endIndex; i++)

{

    File googleFile = filteredFiles.get(i);

    String downloadUrl = this.getUrl(

        googleFile.getId(),

        googleFile.getName(),

```

```

        googleFile.getFileExtension(),

        true);

String previewUrl = this.getUrl(

        googleFile.getId(),

        googleFile.getName(),

        googleFile.getFileExtension(),

        false);

ExternalDigitalAsset externalAsset = new
ExternalDigitalAsset();

externalAsset.setLabelDescription(

        this.getLabelDescription(

                googleFile.getName(),

searchRequest.getHome().getRepository().getLocales()));

externalAsset.setURL(previewUrl);

externalAsset.setThumbnailURL(googleFile.getThumbnailLink());

externalAsset.setDownloadURL(downloadUrl);

externalAsset.setExtension(googleFile.getFileExtension());

externalAsset.setAssetType(googleFile.getFileExtension());

externalAsset.setId(googleFile.getId());

externalAsset.setPhysicalName(googleFile.getName());

externalAsset.setCreationDate(new
Date(googleFile.getCreatedTime().getValue()));

```

```

        externalAsset.setLastUpdatedDate(new
Date(googleFile.getModifiedTime().getValue()));

        externalAsset.setFileSize(new
BigDecimal(googleFile.getSize().longValue()));

        Map<String, String> metaDataMap = new HashMap<>();

        metaDataMap.put("mKey1", "mValue1");

        metaDataMap.put("mKey2", "mValue2");

        externalAsset.setMetaDatas(metaDataMap);

        externalAsset.setWidth(new Integer(300));

        externalAsset.setHeight(new Integer(200));

        externalAssets.add(externalAsset);
    }

    result.setAssets(externalAssets);
}

catch (Exception ex)

{

    throw new RuntimeException(ex);

}

return result;

```

```
}
```

Asset creation

```
public ExternalDigitalAsset createAsset(ExternalUploadAssetRequest
request)

{

    ExternalDigitalAsset asset = new ExternalDigitalAsset();

    File googleFile = new File();

    FileResource fileResource = request.getFileResource();

    String fileName = fileResource.getFile().getName();

    googleFile.setName(fileName);

    FileContent mediaContent = new FileContent(

        new MimetypesFileTypeMap().getContentType(fileName),

        fileResource.getFile());

    try

    {

        File googleFileUploaded = this.googleDrive.files()

            .create(googleFile, mediaContent)

            .setFields("")

            .execute();

        asset.setId(googleFileUploaded.getId());

        asset.setPhysicalName(googleFileUploaded.getOriginalFilename());

        asset.setThumbnailURL(googleFileUploaded.getThumbnailLink());
```

```

        asset.setLabelDescription(

            this.getLabelDescription(

                googleFileUploaded.getName(),

                request.getHome().getRepository().getLocales()));

    }

    catch (IOException ex)

    {

        throw new RuntimeException(ex);

    }

    return asset;

}

```

Asset deletion

```

public OperationExecutionStatus deleteAsset(

    ExternalSingularRequest request,

    boolean isPhysicalDelete)

{

    OperationExecutionStatus status = new OperationExecutionStatus();

    try

    {

        this.googleDrive.files().delete(request.getExternalId()).execute();
    }

```

```

    }

    catch (IOException ex)

    {

        status = new OperationExecutionStatus(new
DAMException(ex.getMessage()));

    }

    return status;

}

```

Asset retrieval

```

public ExternalDigitalAsset getAsset(ExternalSingularRequest request)
throws DAMException

{

    ExternalDigitalAsset digitalAsset = new ExternalDigitalAsset();

    try

    {

        File file = this.googleDrive.files()

            .get(request.getExternalId())

            .setFields("")

            .execute();

        String urlDownload = this

            .getUrl(file.getId(), file.getName(), file.getFileExtension(),
true);

```

```

        String previewUrl = this

            .getUrl(file.getId(), file.getName(), file.getFileExtension(),
false);

        digitalAsset.setId(file.getId());

        digitalAsset.setPhysicalName(file.getOriginalFilename());

        digitalAsset.setLabelDescription(

            this.getLabelDescription(

                file.getName(),

                request.getHome().getRepository().getLocales()));

        digitalAsset.setURL(previewUrl);

        boolean isImage =
DigitalAssetExtension.parseExtension(file.getFileExtension())

            .getDigitalAssetContentType()

            .isImage();

        if (isImage)

        {

            digitalAsset.setThumbnailURL((previewUrl));

        }

        else

        {

            digitalAsset.setThumbnailURL(file.getThumbnailLink());

        }

```



```

        digitalAsset.setDownloadURL(urlDownload);

        digitalAsset.setAssetType(file.getFileExtension());

        digitalAsset.setExtension(file.getFileExtension());

        digitalAsset.setCreationDate(new
Date(file.getCreatedTime().getValue()));

        digitalAsset.setLastUpdatedDate(new
Date(file.getModifiedTime().getValue()));

        digitalAsset.setFileSize(new
BigDecimal(file.getSize().longValue()));

        Map<String, String> metaDataMap = new HashMap<>();

        metaDataMap.put("mKey1", "mValue1");

        metaDataMap.put("mKey2", "mValue2");

        digitalAsset.setMetaDatas(metaDataMap);

        digitalAsset.setWidth(new Integer(300));

        digitalAsset.setHeight(new Integer(200));

    }

    catch (IOException ex)

    {

        throw new DAMException(ex);

    }

    return digitalAsset;

}

```

```

public List<ExternalDigitalAsset> getAssets(ExternalPluralRequest
externalRequest)

{

    List<ExternalDigitalAsset> externalAssets = new ArrayList<>();

    for (String externalId : externalRequest.getExternalIds())

    {

        try

        {

            File file;

            try

            {

                file =
this.googleDrive.files().get(externalId).setFields("*").execute();

            }

            catch (Exception ex)

            {

                continue;

            }

            ExternalDigitalAsset externalDigitalAsset = new
ExternalDigitalAsset();

            externalDigitalAsset.setId(file.getId());

```

```

externalDigitalAsset.setPhysicalName(file.getOriginalFilename());

        externalDigitalAsset.setCreationDate(new
Date(file.getCreatedTime().getValue()));

        externalDigitalAsset

                .setLastUpdatedDate(new
Date(file.getModifiedTime().getValue()));

        externalDigitalAsset.setLabelDescription(

                this.getLabelDescription(

                        file.getName(),

externalRequest.getHome().getRepository().getLocales()));

        String urlDownload = this

                .getUrl(file.getId(), file.getName(),
file.getFileExtension(), true);

        String previewUrl = this

                .getUrl(file.getId(), file.getName(),
file.getFileExtension(), false);

        externalDigitalAsset.setURL(previewUrl);

        externalDigitalAsset.setThumbnailURL(file.getThumbnailLink());

        externalDigitalAsset.setWidth(new Integer(300));

        externalDigitalAsset.setHeight(new Integer(200));

        externalDigitalAsset.setDownloadURL(urlDownload);

        externalDigitalAsset.setAssetType(file.getFileExtension());

        externalDigitalAsset.setExtension(file.getFileExtension());

```

```

        Map<String, String> metaDatas = new HashMap<>();

        metaDatas.put("metadata1", "metadata1");

        metaDatas.put("metadata2", "metadata2");

        externalDigitalAsset.setMetaDatas(metaDatas);

        externalDigitalAsset.setTags(Arrays.asList("tag1", "tag2"));

        externalAssets.add(externalDigitalAsset);
    }

    catch (IOException ex)

    {

        throw new RuntimeException(ex);

    }

}

return externalAssets;

}

```

Asset tags

```

public ExternalTagResult getTags(ExternalCommonRequest request)

{

    ExternalTagResult externalTagResult = new ExternalTagResult();

```

```

        Tag tag1 = new Tag();

        tag1.setCode("tag1");

        tag1.setFontSize("14");

        externalTagResult.getTags().add(tag1);


        Tag tag2 = new Tag();

        tag2.setCode("tag2");

        tag2.setFontSize("16");

        externalTagResult.getTags().add(tag2);


        return externalTagResult;

    }

```

Sample definition class

The following code sample shows how to instantiate the class you implemented above.

Additionally, note that you can use the `allowUpload()` to determine whether users can upload to the external storage location.

```

import com.orchestranetworks.addon.dama.externalmanagement.*;


public final class ExternalGoogleManagerDefinition extends
ExternalManagerDefinition

{

    // Creates a new ExternalManager based on your implementation

```

```
public ExternalManager getExternalManager()

{

    return new ExternalGoogleManager();

}


// Determines whether upload to the external storage location is
enabled

public boolean allowUpload()

{

    return true;

}


}
```

Registering your manager class

You can register your custom class either on repository startup or by running a service in the UI. For information on how to declare a module (for startup registration) or declare a user service, please see the *TIBCO EBX® Developer Guide*.

Including third-party resources

Any resources required by a third-party should be added to the same location as your `ebx.jar` file. As shown below the required libraries for the Google Drive API are deployed in Tomcat along with EBX®.



Java API Reference

- [TIBCO EBX® Add-ons 4.5.22 Java API](#)

Reference Guide

- Add-on specific services
- Digital asset group
- Drive group
- D.A.C. group
- Classification group
- Reference data group

Add-on specific services

Overview of add-on specific services

The TIBCO EBX® Digital Asset Manager Add-on provides several custom services that allow you to perform asset management-specific actions. To access these services open the **Actions** menu for the specified dataset, or table. The following describes the location of each service and its scope:

TIBCO EBX® Digital Asset Manager Add-on dataset

NAME/LOCATION/SCOPE	DESCRIPTION
The Migrate digital asset manager data service applies to the dataset.	Migrates previous add-on versions to the latest version.
The Create D.A.C. for data model service applies to the dataset.	Automatically creates a D.A.C. for a data model you specify. Before running the service, ensure that the data model contains a 'media type' field.
The Manage digital assets service applies to all assets in all Drives.	Allows you full control over any asset in any Drive.
The Backup service applies to the dataset.	Creates a backup of your digital assets.
The Restore service applies to the dataset.	Allows you to restore digital assets.

Drivetable

NAME/LOCATION/SCOPE	DESCRIPTION
The Delete all digital assets in selected drive(s) service applies to selected records.	Deletes all digital assets contained in the selected Drives.
Change physical root path	Allows you to change the selected Drive's physical root path.

Digital assettable

NAME/LOCATION/SCOPE	DESCRIPTION
Identify unused assets	Locates any unused assets and filters the table display so that only those records display. An unused asset is one that is not attached to a field.
Import from a ZIP file	Allows you to perform a bulk import of assets from a ZIP file.
The Create new version service applies to selected records.	Creates a new version of the selected asset.
The Upload new digital asset service applies to the table.	Allows you to upload a new digital asset.
The Deactivate (Logical delete) service applies to selected records.	Changes the selected asset's state to 'Deactivated'. You can return the asset to 'Activated', or another state by opening the asset and using the 'State' drop-down list.
The Permanently delete (Physical delete) service applies to selected records.	Physically removes the digital asset from the Drive.

Digital asset versiontable

NAME/LOCATION/SCOPE	DESCRIPTION
The Create new version service applies to the table.	Allows you to upload a new version of an asset.

NAME/LOCATION/SCOPE	DESCRIPTION
The Delete digital asset version applies to selected records.	Physically removes the digital asset version.

Digital asset group

Overview

This group contains information about any digital asset under add-on management.

Digital asset, Digital asset version, and Metadata value tables

When you open a record in the **Digital asset** table, tabs display that contain the same information as the corresponding table. The following table describes each property.

Informationtab/Digital Assettable

PROPERTY	DEFINITION
Physical name	The asset's original file name.
Label and description	An asset's label and description.
Creation date	Shows the asset creation date — the date when the asset was added to the add-on control.
Last update date	Date of the last update to this asset.
Digital asset type	Indicates the asset type.
File extension	Displays the asset's file extension.
State	An asset's current state value.
Drive	Location of this asset.

Version managementtab/Digital asset versiontable

PROPERTY	DEFINITION
Physical name	Displays the asset's file name.
Storage date	Date on which the asset was uploaded to a Drive.
Digital asset	The digital asset of which this is a version.
User profile author	Indicates who added this asset to the add-on.
Version name	Lists any versioning applied to this asset (1.0, 2.0, etc.).
Comment	Displays comments applied to this asset version.
Current version	Indicates whether this version is considered the current version.

Metadatatab/Metadata valuetable

PROPERTY	DEFINITION
Digital asset	The digital asset to which this metadata applies.
Metadata nature	Displays the metadata nature applied to this digital asset.
Value	Holds the metadata value applied to this asset.

Tagstab

PROPERTY	DEFINITION
Tags	Displays the tags attached to the selected asset.

Drive group

- [Overview](#)

- Drive table
- Image configuration

Overview

The **Drive group** contains tables for Drive and image configuration.

Drive table

This table defines a Drive, or asset storage location. After creating a Drive, you can link it with a data model field using a **Digital asset component**. This enables the selected field access to assets stored in the Drive.

PROPERTY	DEFINITION
Drive id	Id of drive.
Label and description	Defines the label and description for this Drive.
Drive type	Specifies whether the Drive points to a local or network location, or to an externally managed storage location. Connections to external locations, require implementation of the add-on's API and any additional third-party requirements. See the add-on's <i>Developer Guide</i> for more details.
Physical root path	Specifies the path to this Drive's storage location. This location stores all assets and asset versions uploaded to this Drive.

User permissiongroup

PROPERTY	DEFINITION
Restriction policy	Defines whether the permission is restrictive or not. For all user-defined permission rules that match the current user session: If some rules having restrictions are defined, the minimum permissions of these restricted rules are applied; if no rule having restrictions are

PROPERTY	DEFINITION
	defined, the maximum permissions of all matching rules are applied.
Profile	User profile to which this set of permissions applies.
Allow to upload new asset	Determines whether the chosen profile can upload files to this Drive.
Allow to upload new version	Determines whether users associated with the specified profile can upload new versions of assets.
Allow to change current version	Determines whether users associated with the specified profile can choose which asset is considered the current version. If users are allowed to upload new assets, this property defaults to 'Yes'. If you set this to 'No', the most recently uploaded asset is considered the current version.
Allow to share and download	Determines whether users associated with the specified profile can download and/or share the asset via email.
Allow to delete	Determines whether the chosen profile can delete files in this Drive.
Allow to view digital asset of other user	Determines whether users associated with the specified profile can view assets uploaded by other users.
Maximum allowed file size	Specifies the largest file size (in MBs) that the selected profile can upload to this Drive.
Max usable space	Caps the amount of usable disk space for a Drive that uses this configuration. Once storage reaches this threshold, users cannot upload additional files, unless files are physically deleted.

PROPERTY	DEFINITION
Physical used space	Amount of disk space used by assets in this Drive.
Physical free space	Amount of disk space remaining.
Image configuration	Specifies the image configuration used by this Drive. The image configuration sets a maximum width and height for uploaded images.
Restrict file upload	Determines whether file type restrictions apply by default for a Digital Asset Component (D.A.C.) that uses this Drive. By default, the add-on does not limit upload to specific file types. With this option enabled, you can select allowed file types when creating a D.A.C. that uses this Drive. Note that you can override this option when creating a D.A.C.
Blacklisted extensions	The add-on blocks any extensions you list here. Separate entries using a comma, semicolon, period or whitespace. For example: <code>exe, msi, sh, bat</code>
Encrypt files	When activated, the add-on encrypts files and thumbnails before storing in the file system. The add-on automatically decrypts these files before displaying or allowing users to download. Note that you cannot modify this field after saving.

Image configuration

This table allows you to create configurations that set limits on the width and height of uploaded images. These settings can be applied to *Drive configurations*.

PROPERTY	DEFINITION
Code	Specifies a unique value to identify this configuration.

PROPERTY	DEFINITION
Label and description	Defines the label and description for this configuration.
Max width	Sets the maximum width for images uploaded to a Drive that uses this configuration.
Max height	Sets the maximum height for images uploaded to a Drive that uses this configuration.

D.A.C. group

- [Overview](#)
 - [Digital asset component table](#)
 - [View configuration table](#)

Overview

The **Digital asset component (D.A.C.)** group allows you to create a link between a data model field to which you want to attach assets and a physical storage location. Additionally, you can configure mosaic look and feel.

Digital asset component table

This table allows you to configure a **Digital asset component**, which links a data model field with a Drive.

PROPERTY	DEFINITION
Code	Specifies a unique value to identify this D.A.C.
Label and description	Defines the label and description for this D.A.C.
Drive	Specifies the Drive used as the storage location for this configuration.

PROPERTY	DEFINITION
Restriction policy	Defines whether the permission is restrictive or not. For all user-defined permission rules that match the current user session: If some rules having restrictions are defined, the minimum permissions of these restricted rules are applied; if no rule having restrictions are defined, the maximum permissions of all matching rules are applied.
Profile	User profile to which this set of permissions applies.
Allow to upload new asset	Determines whether the chosen profile can upload files to this Drive.
Allow to upload new version	Determines whether users associated with the specified profile can upload new versions of assets.
Allow to change current version	Determines whether users associated with the specified profile can choose which asset is considered the current version. If users are allowed to upload new assets, this property defaults to 'Yes'. If you set this to 'No', the most recently uploaded asset is considered the current version.
Allow to open Editor	Determines user is allowed to open Editor from field in D.A.C.
Allow to share and download	Determines whether users associated with the specified profile can download and/or share the asset via email.
Allow to delete	Determines whether the chosen profile can delete files in this Drive.
Allow to detach	Determines whether a user can detach assets from fields.

PROPERTY	DEFINITION
Allow to view digital asset of other user	Determines whether users associated with the specified profile can view assets uploaded by other users.
Allow to quick upload and attach	Determines whether users can choose to skip intermediate steps when uploading and attaching assets.
Maximum allowed file size	Specifies the largest file size (in MBs) that the selected profile can upload to this Drive.
Image configuration	Specifies the image configuration used by this D.A.C. The image configuration sets a maximum width and height for uploaded images.
Data model	Specifies the data model containing the field you want to connect to the specified Drive.
Field path	Defines the path to the field you want to connect to the specified Drive.
Custom filter	This optional property accepts a custom filter implemented in a Java class. The filter can specify that only assets meeting certain criteria display in the Editor. The filter class you create your must implement the predefined interface (<pre>com.orchestranetworks.addon.dama.ext.EditorFilter)</pre> This interface's <code>accept()</code> method filters assets from the Editor. If you decide to create a custom filter class, set the class value to D.A.C record and be sure the class implements the <code>EditorFilter</code> interface. The value filter depends on the record's fields.
Restrict file upload	Determines whether to apply file type restrictions. By default, the add-on does not limit upload to specific file types. With this option enabled, you can select allowed file

PROPERTY	DEFINITION
	types when creating a D.A.C. that uses this Drive.
Blacklisted extensions	The add-on blocks any extensions you list here. Separate entries using a comma, semicolon, period or whitespace. For example: <code>exe, msi, sh, bat</code>
Supported extensions	Enables upload of the selected extensions. This field only displays when you enable the Restrict file upload option.
Display configuration	Sets the display configuration used by this D.A.C. which determines how assets display when attached to the data model field.
Table view configuration	The configuration for view digital asset on the table.
Editor configuration	Determines the default layout for the 'Editor' view.
Tag cloud	Specifies which tag cloud is used for this D.A.C.

View configuration table

This table allows you to set asset display options.

PROPERTY	DEFINITION
Label and description	Defines this configuration's label and description.
View mode	Determines whether assets display in a tiled mosaic, list view, or table view.
Display attached assets	Determines whether assets display as their associated icon, or thumbnails of the asset.

PROPERTY	DEFINITION
Always display quick actions	Determines whether the quick actions buttons are always visible on asset thumbnails.
Expand attached asset	Allows users to expand/collapse asset thumbnails.
Thumbnail width	Determines the width of the asset thumbnail.
Thumbnail height	Determines the height of the asset thumbnail.
Display label under thumbnail	Determines whether the assets label displays in the mosaic.
Vertical scroll	Determines whether the mosaic scrolls vertically or horizontally.
Number of assets per row	Sets the number of assets displayed in the mosaic's rows. Note that this property can affect overall width of the mosaic.
Number of assets per column	Sets the number of assets displayed in the mosaic's columns. If additional assets are loaded, a scroll bar enables navigation.

Classification group

- [Overview](#)
 - [Tag table](#)
 - [Digital asset by tag](#)
 - [Tag cloud table](#)

Overview

The **Classification group** stores all tags and tag clouds that you can apply to assets and D.A.C.'s. The **Digital asset by tag** table also provides you with a hierarchical view of each tag and the assets to which they have been applied.

Tag table

This table stores all tags. If you have administrative privileges, you can create new tags by adding records to this table. All tags must be unique.

PROPERTY	DEFINITION
Code	Defines this tag.

Digital asset by tag

Contains relationships to show a hierarchical view of tags and related assets.

PROPERTY	DEFINITION
Digital asset	Identifies the digital asset.
Tag	Associates this tag with the digital asset.

Tag cloud table

The **Tag cloud** table stores the label and description for each tag cloud. A tag can be associated with multiple tag clouds. When you open a tag cloud, a view of associated tags displays. From this view, you can create new tags and use the **Actions** menu to:

- Attach an existing tag to this tag cloud. Only tags not currently attached to a cloud display for attachment.
- Detach one or more selected tags from this tag cloud.
- Delete one or more selected tags.
- Duplicate a tag. However, each tag must be unique. Before saving the tag, you must update it.
- Move one or more selected tags to a different tag cloud.

PROPERTY	DEFINITION
Label and description	Applies the label and description to this tag cloud.

Reference data group

- [Overview](#)
 - [Metadata nature table](#)
 - [Digital asset type](#)
 - [Drive type table](#)
 - [File extension table](#)
 - [State table](#)
 - [History table](#)

Overview

Tables in the **Reference data group** define values that other EBX® Digital Asset Manager Add-on components can use.

Metadata nature table

This table allows you to create categories of metadata. You can add these categories to digital assets. After applying metadata nature you can further enrich the asset with a data value.

PROPERTY	DEFINITION
Code	Specifies a unique value to identify this metadata nature.
Label and description	Defines the label and description for the metadata category.

Digital asset type

This table contains the available types of digital assets.

PROPERTY	DEFINITION
Code	Specifies a unique value to identify a type of digital asset.

PROPERTY	DEFINITION
Business code	A business friendly identifier for a digital asset type.
Label and description	Label and description used by a digital asset type.

Drive type table

This table lists available Drive types.

PROPERTY	DEFINITION
Code	Specifies a unique value to identify a Drive type.
Label and description	Defines the label and description for a Drive type.

File extension table

This table stores available file extensions. The **Supported extensions** field in a D.A.C. specifies which extensions users can attach to fields. This table includes several default extensions, but allows you to create additional extensions to meet your business requirements.

PROPERTY	DEFINITION
Business code	A business identifier for a file extension.
Filename extension	Specifies a unique value to identify the file extension format.
Label and description	Defines the file extension's label and description.
Digital asset type	Specifies what type of digital asset this file extension type is.
Mime type	Optional information for this file extension.

PROPERTY	DEFINITION
Icon	Sets the icon for this type of file extension. You can upload and store files for use as icons.

State table

This table lists available states. States determine whether an asset is active, or inactive. Only active assets can be viewed in the **Editor** or from the **Manage digital assets** view.

PROPERTY	DEFINITION
Code	Specifies a unique value to identify a state.
Label and description	Defines the label and description for a state.

History table

The history table stores actions related to a digital asset.

PROPERTY	DEFINITION
User profile	User profile that made changes to the specified asset.
Digital asset	Asset changes were applied to.
Old state	The asset's previous state.
New state	The asset's new state.
Changed date	Date changes were made to the asset.

Release Notes

- [Version 1.8.29](#)
- [All release notes](#)

Version 1.8.29

- [New features](#)
- [Changes in Functionality](#)
- [Changes to third-party libraries](#)
- [Closed Issues](#)
- [Known Issues](#)

New features

This release contains the following new features and updates:

- The `Servlet` version was updated to 3.1.
- Digital asset delivery via the API now uses a secured REST endpoint: `/asset-content/provider`. This replaces the legacy servlet-based pattern (e.g. `/ebx-addon-dama/AssetProvider`). Unauthenticated asset links distributed in the past no longer work. Update any existing integrations that use the legacy servlet URLs to use the new REST endpoint.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The Spring Web MVC framework was updated to version 5.3.39.

The Apache Commons Lang library was updated to 3.18.0

The Apache Commons FileUpload library was updated to version 1.6.0

The Apache Commons IO library was updated to version 2.20.0.

The Google Gson library was updated to version 2.13.2.

Closed Issues

This release contains the following closed issues:

- Digital assets are accessible via URL without having to log into EBX®.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

All release notes

- Version 1.8.29
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.28
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.27
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.26
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.25
 - New features

- Changes in Functionality
- Changes to third-party libraries
- Closed Issues
- Known Issues
- Version 1.8.24
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.23
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.22
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.21
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues

- Version 1.8.20
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.19
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.18
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.17
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.16
 - New features
 - Changes in Functionality
 - Changes to third-party libraries

- Closed Issues
- Known Issues
- Version 1.8.15
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.14
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.13
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.12
 - New features
 - Changes in Functionality
 - Changes to third-party libraries
 - Closed Issues
 - Known Issues
- Version 1.8.11

- Library Updates
- Version 1.8.10
 - Updates
 - Bug fixes
- Version 1.8.9
 - Product updates
 - Bug fixes
- Version 1.8.8
 - Product updates
 - Bug fixes
- Version 1.8.7
 - Product updates
 - Bug fixes
- Release Notes 1.8.6
 - Bug fixes
- Release Notes 1.8.5
 - Updated features
 - Bug fixes
- Release Notes 1.8.4
 - New features and updates
- Release Notes 1.8.3
 - Updated features
- Release Notes 1.8.2
 - New features and updates
- Release Notes 1.8.1

- Updated behavior
- Release Notes 1.8.0
 - New features and updates
 - Known limitations
 - Bug fixes
- Release Notes 1.7.0
 - New features and updates
 - Bug fixes
- Release Notes 1.6.0
 - New features and updates
 - Bug fixes
- Release Notes 1.5.1
 - Featured updates
 - Bug fixes
- Release Notes 1.5.0
 - New features and updates
 - Bug fixes
- Release Notes 1.4.3
 - Featured updates
 - Bug fixes
- Release Notes 1.4.2
 - Featured updates
- Release Notes 1.4.1
 - Bug fixes
- Release Notes 1.4.0
 - New features

- Known limitations
- Bug fixes
- Release Note 1.3.0
 - Overview of features and enhancements
 - Bug fixes
- Release Note 1.2.2
 - New features
- Release Note 1.2.1
 - New features
- Release Note 1.2.0
 - New features
 - Bug fixes
- Release Note 1.1.1
 - Bug fixes
- Release Note 1.1.0
 - New features
 - Bug fixes
 - Warnings
- Release Note 1.0.2 fix 001
 - Bug fixes
 - Warnings
- Release Note 1.0.3
 - Bug fixes
- Release Note 1.0.2
 - New features
 - Bug fixes

- [Release Note 1.0.1](#)
 - [New features](#)
- [Release Note 1.0.0](#)
 - [New features](#)

Version 1.8.29

New features

This release contains the following new features and updates:

- The `Servlet` version was updated to 3.1.
- Digital asset delivery via the API now uses a secured REST endpoint: `/asset-content/provider`. This replaces the legacy servlet-based pattern (e.g. `/ebx-addon-dama/AssetProvider`). Unauthenticated asset links distributed in the past no longer work. Update any existing integrations that use the legacy servlet URLs to use the new REST endpoint.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The Spring Web MVC framework was updated to version 5.3.39.

The Apache Commons Lang library was updated to 3.18.0

The Apache Commons FileUpload library was updated to version 1.6.0

The Apache Commons IO library was updated to version 2.20.0.

The Google Gson library was updated to version 2.13.2.

Closed Issues

This release contains the following closed issues:

- Digital assets are accessible via URL without having to log into EBX®.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.28

New features

This release includes the new `ebx.addon.dama.convert.officeFiles.to.pdf` property. By default, this property is set to `true` and it determines whether assets that are Microsoft Office files get automatically converted to PDFs on start up. See [Disabling automatic asset to PDF conversion](#) for more information.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The following third-party libraries were updated:

- The Apache Commons Compress library was updated to version 1.26.0.
- The Apache Commons IO library was updated to version 2.12.0.

Closed Issues

The conversion of assets to PDFs increases the EBX® boot time.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.

- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.27

New features

This release contains no new features.

Changes in Functionality

The REST requests to attach and detach assets from records were updated to use Content-type: multipart/form-data.

Changes to third-party libraries

The FasterXML jackson-databind library was updated to version 2.16.0.

Closed Issues

This release contains the following closed issues:

- An error displays when creating a new record in the **Metadata** that has an empty **Value** field.
- Errors occur when uploading DOCX files using the API.
- [Tomcat](#) Errors occur when uploading and previewing DOCX files.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.

- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.26

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The following third-party libraries were updated:

- The FasterXML jackson-databind library was updated to version 2.15.2.
- The Batik All library was updated to version 1.17.

Closed Issues

User cannot upload an asset when using the API.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.25

Released: July 2023

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The following third-party libraries were updated:

- The jQuery library was updated to version 3.6.4.
- The Spring framework was updated to version 5.2.24.

Closed Issues

A HTML block is displayed instead of rendering the activation of the uploading attachment.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.

- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.24

Released: April 2023

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The following third-party libraries were updated:

- The Zip4j library was updated to version 2.11.3.
- The Apache Commons FileUpload library was updated to version 1.5.

Closed Issues

This release contains the following closed issues:

- Previews for PPT and PPTX files do not work.
- Assets cannot be attached using the `upload` or `internal-upload` endpoints.
- Startup of EBX is overruling information search config for DAMA add-on.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.23

Released: January 2023

New features

Instructions were added to the documentation that describe how to prevent library conflicts when deploying on WebLogic. See the *Preventing library conflicts on WebLogic* heading in the

`index.html` file that is located in the following folder in the 4.5.16 Add-on Bundle: *documentation*
> *dama_<xxx>*.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

This release contains no changes to third-party libraries.

Closed Issues

This release contains no closed issues.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.

- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.22

Released: December 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The following third-party libraries were updated:

- The Apache Batik library was updated to version 1.16.
- The Apache FOP All In One library was updated to version 2.8.

Closed Issues

The add-on now utilizes the Docx4j library instead of Itext to manipulate its files.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.

- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.21

Released: October 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The following third-party libraries were updated:

- The Apache Taglibs library was removed.
- The Apache Xalan library was removed.
- The Apache Batik library was updated to version 1.15.
- The FasterXML jackson-databind library was updated 2.14.0-rc2.

Closed Issues

A vulnerability needs to be fixed.

Known Issues

This release contains the following known issues:

- DOCX files do not display correctly in previews.
- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.20

Released: August 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The following third-party libraries were updated:

- The Apache PDFBox libraries were updated to version 2.0.26.
- The jQuery UI library was updated to version 1.13.2.

Closed Issues

This release contains no closed issues.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.

- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.19

Released: August 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

The Apache POI library was updated to version 5.2.2.

Closed Issues

This release contains the following closed issues:

- An error occurs when uploading PPTX files.
- The asset's label displays incorrectly.
- The preview for SVG files does not work correctly.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.18

Released: May 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no changes in functionality.

Changes to third-party libraries

This release contains the following updates to third-party libraries:

- The zip4j library was updated to version 2.10.0.
- The Spring framework was updated to version 5.2.22.

Closed Issues

This release contains the following closed issues:

- Asset preview does not work correctly.
- Asset download does not work correctly.
- Asset's **Digital asset type** does not set correctly.
- Asset thumbnails are not blurred after selecting the **Detach** icon.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.

- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.17

Released: April 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no functionality changes.

Changes to third-party libraries

This release contains the following updates to third-party libraries:

- The FasterXML/jackson-databind library was updated to version 2.13.2.1.
- The Spring framework was updated to version 5.2.20.

Closed Issues

This release contains no closed issue.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.

- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.16

Released: March 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no functionality changes.

Changes to third-party libraries

This release contains the following updates to third-party libraries:

- The Apache PDFBox and Apache FontBox were updated to version 2.0.25.
- The Spring framework was updated to version 5.2.19.
- The jQuery UI and UI widget libraries were updated to version 1.13.1.
- The jQuery library was updated to version 3.6.0.

- The Apache XML Graphics Commons library was updated to version 2.7.
- The Zip4j library was updated to version 2.9.1.

Closed Issues

This release contains the following closed issues:

- Users should not delete a type that has the prefix.
- A Javascript error occurs if users scroll up and down the scroll bar on the full-screen when previewing a DOC file that is smaller than 5MB.
- A `StringIndexOutOfBoundsException` occurs when the **Table view configuration** is set to table view and the language is French.
- When the input is both encoded and decoded, the metadata nature value cannot be modified.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.

- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.15

Released: January 2022

New features

This release contains no new features.

Changes in Functionality

This release contains no functionality changes.

Changes to third-party libraries

This release contains no updates to third-party libraries.

Closed Issues

This release contains the following closed issues:

- Users can attach assets that are blacklisted and have unsupported extension types.
- The displayed error message is incorrect in the **File extension** table's **Filename extension** property.
- An error occurs when a video asset is deleted while a users is previewing it.
- The previews of document files do not display correctly.
- The **Attachments** pane does not display correctly when it displays the scrollbar.
- Tags created in the add-on's administrative area do not display in the **Digital Asset Manager - Edit** screen.
- Increased start up time is caused by refreshing schemas when the add-on is initialized.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.14

Released: December 2021

New features

This release contains no new features.

Changes in Functionality

This release contains no functionality changes.

Changes to third-party libraries

The following changes were made to third-party libraries:

- The Spring Framework was updated to version 5.2.15.
- The jQuery UI library was updated to version 1.13.0.

Closed Issues

This release contains the following closed issues:

- Validate input values to treat special characters as normal strings.
- Validate field inputs in the **Upload new digital asset** screen.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.

- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.13

Released: October 2021

New features

This release contains no new features.

Changes in Functionality

This release contains no functionality changes.

Changes to third-party libraries

This release contains no updates to third-party libraries.

Closed Issues

This release contains the following closed issues:

- Vietnamese text does not display properly when previewing DOC, DOCX, PPT, and PPTX files.
- Previews of PDF files do not display all PDF elements.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.

- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- When running on Linux, the font used in DOCX, PPT, and PPTS files must be installed previous to uploading these assets. Otherwise, Vietnamese text does not display correctly in asset previews.
- Vietnamese text does not display correctly when viewing previews of DOC assets.
- PDF previews might not display correctly when using Internet Explorer.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.12

Released: August 2021

New features

When using the filter's search feature in the **Editor**, the TIBCO EBX® Information Search Add-on must be activated and have a valid license. If this is not the case, an error message now displays to guide users.

Changes in Functionality

This release contains no functionality changes.

Changes to third-party libraries

This release contains the following third-party updates:

- The Apache PDFBox, Preflight, pdfbox-tools, and XmpBox libraries were updated to version 2.0.24.
- Apache Commons Compress to version 1.21.

Closed Issues

This release contains no closed issues.

Known Issues

This release contains the following known issues:

- Searching for assets in the media-type field using quick search is not supported. However, when previewing some file types, such as PDFs, you can search for text within the file.
- When updating asset information in a child dataset, the parent dataset automatically updates also.
- The **Deactivated** state is available for users without sufficient rights to deactivate an asset.
- User can import a new version in 'Version management' tab from 'Information' button when 'Import new version' service is disabled.
- A user can import a new version of an asset without sufficient permissions.
- Confirm message is displayed after clicking on 'Download' button on the child dataset.
- The configuration is not updated for the supported file extensions after users access the Digital Asset Manager widget.
- The progress bar does not work properly when importing from a ZIP file.
- Document previews cannot display Vietnamese text.
- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Thumbnails of some uploaded SVG files do not display correctly.

Version 1.8.11

Released: June 2021

Library Updates

Spring Data was removed from `ui-framework-dependencies.jar`.

Version 1.8.10

Released: May 2021

Updates

This release contains the following updates:

- The Apache PDFBox, PDFBox-tools, FontBox, preflight and XmpBox libraries were updated to version 2.0.23.
- The jai-imageio library was updated to version 1.4.0.
- The Zip4j library was updated to version 1.3.3.
- The Scripts.bundle.js library was removed.
- The Apache Commons IO library was updated to version 2.8.0.

Bug fixes

This release contains the following bug fixes:

- The **Backup** service does not work correctly when inputting a space into the **Backup file name** field.
- If there is a validation error, the **Backup** screen cannot be closed when running the **Backup** service.
- The preview screen displays DOC, DOCX, PPT, and PPTX files incorrectly when they are smaller than 5MB. This happens when accessed from the following places: **Media type field**, **Editor**, **Edit digital asset**, **Manage digital assets**.
- The thumbnail displays incorrectly and a JavaScript error occurs when uploading a DOC file that is larger than 5MB.
- The zoom icon does not work on the **Manage digital asset** screen.
- The asset filter in the EBX® search form's tabular view is not stable.

Version 1.8.9

Released: March 2021

Product updates

- The `DriveManager.getDigitalAsset()` API was deprecated and replaced with `getDigitalAssetOrNull()`, which returns null if the requested asset does not exist.
- The Apache HttpClient library was upgraded to version 4.5.13 and Batik to version 1.14.
- An update was applied to correct an issue with the Apache Standard Taglibs library.

Bug fixes

- The thumbnail is not properly generated or not generated at all after uploading an SVG file.
- The thread is not stopped when Tomcat Server is stopped.
- There is an issue when uploading an SVG file to a Drive with version 1.8.7 of the add-on.

Version 1.8.8

Released: February 2021

Product updates

Google Guava was updated to version 30.1.

Bug fixes

An exception occurs in the add-on when using the Manage digital asset service.

Version 1.8.7

Released: January 2021

Product updates

This release contains the following library updates:

- Apache Standard Taglibs to version 1.2.3.
- Spring framework to version 5.2.9.
- Jackson Databind to version 2.11.2.
- Batik XML utility library to version 1.13.
- Apache Common Codec to version 1.13.

Bug fixes

Absolute URLs are not calculated as expected.

A NullPointerException is thrown while starting EBX.

Release Notes 1.8.6

Release Date: October 20, 2020

Bug fixes

A complete URL is required when sharing an asset by email.

Release Notes 1.8.5

Release Date: September 18, 2020

Updated features

This release contains the following feature updates:

- The following library updates were made: jQuery to v3.5.0, jQuery UI to v1.12.1, jQuery fileupload to v10.31, and Apache POI to v4.1.2. Additionally, DOCCConverter, OfficeConverter, PPTConverter, and PPTXConverter were updated.
- Support for the OpenJDK8 and Open JDK11 libraries has been included.

Bug fixes

The log was updated from INFO to DEBUG mode to display more readable results.

Release Notes 1.8.4

Release Date: June 23, 2020

New features and updates

This release contains the following feature updates:

- The add-on now provides administrators the option to activate assets when viewing them from the **Digital asset** screen. To perform this action, select the **Activated** option from the **Actions** drop-down menu.
- In the **Manage digital assets** screen, the **Drive** drop-down list is now sorted alphabetically.
- File formats listed in the **Blacklisted extensions** property cannot be attached from the **Editor** screen.

- Behavior has been updated to improve consistency in the way error messages display.
- When an administrator moves assets from an encrypted Drive to an unencrypted Drive, the add-on automatically decrypts assets. This functionality applies when moving assets in the opposite manner—decrypted to encrypted.
- The error message shown when users are not able to attach an asset has been updated.
- Support for JDK8 and JDK11 has been updated. Additionally, the docx4j, pdfbox, and jQuery libraries have been updated.

Bug fixes

This release contains the following bug fixes:

- The Esc key does not work correctly when previewing a document file in full-view mode.
- The search page service does not work correctly when previewing document assets.
- The first page of a document file cannot be completely displayed in full-view in the **Editor** or **Manage digital assets** screens.
- With assets that have tags, the **Last updated date** property is updated when saving and closing—even if there is no change to the asset.
- In the **Manage Digital Assets** screen, selected tags are not cleared after changing the Drive.
- Loading issue exceptions that link to the DOCX4J dependency prevent preview of DOCX files on Drives.
- The documentation and tool tips for the **Blacklisted extensions** should reflect the field behavior that listed extensions can also be separated by whitespace, semicolons, or dots.
- An unexpected message is given when users upload DOC/DOCX files (about 300kb) in the UI.
- All Drives are displayed in the **Manage digital assets** screen instead of the defined Drive when running the add-on service on a perspective.
- A NullPointerException is raised when the thumbnail displays an SVG default icon.
- There should be a complete URL for an asset which is shared via email.

Release Notes 1.8.3

Release Date: April 20, 2020

Updated features

When you use the REST API to retrieve an asset's URL, the returned JSON object includes the following new response parameters:

- `preview_url` : The URL of the asset preview.
- `defaulticon` : The URL of the default file extension icon.

Bug fixes

This release contains the following bug fixes:

- When using the add-on's REST API, the value returned in the URL field must be the URL of the original file and not the file preview's URL.
- If the uploaded file is >5MB, a thumbnail image based on the source file must not be generated.
- The DAMException log is updated when attempting to delete an asset that has been removed.
- An asset version cannot be deleted if its binary file has already been deleted.

Release Notes 1.8.2

Release Date: February 20, 2020

New features and updates

This release contains the following feature updates:

- Tooltips have been added for the **Drive** and **Tags** properties when uploading assets.
- PDF files that are less than 5MB can now be previewed.
- When using the API to get an asset's URL, the parameter in the returned JSON object now matches the protocol used in the request.
- The **Editor** can now be used to edit assets when using a TIBCO EBX® Cloud Instance.
- When viewing assets from a storage location managed outside of EBX®, PDF files can now be previewed in the **Editor**.
- If using an externally managed Drive location, the **State** field is now hidden when viewing information about an asset.
- The number of assets that can be included in a single upload has been increased to 300.

- When there are multiple versions of an asset, the displayed file size now updates to the current version of the asset.
- The thumbnail and preview display for SVG files has been updated. If the file includes animation, users can interact with it when previewing.

Bug fixes

This release contains the following bug fixes:

- Duplicated tags are not hidden when users add a tag with a space character, which already exists.
- A `TableTrigger` is fired in the add-on even when there is no change in the record.
- An error message should be raised when uploading assets on the **Editor** screen through a deleted D.A.C.
- A deactivated asset is missing in the attachment pane when it is deactivated from the **Manage digital assets** screen.
- The loading icons are not aligned with other thumbnails in the list when quickly uploading multiple assets from the **Edit digital asset** screen.
- Unexpected behavior occurs when uploading a file to create a new version from the Media type field.
- The API's `UIWidget` to disable modifications in the editor does not work.
- The system is not responsive after double-clicking on assets.
- A null pointer exception is thrown when the `ExternalManager`'s `getTags` API returns null.
- Users cannot preview assets in an external Drive from the **Edit digital asset** screen.
- After changing the label of a dataset, the download button is not available on the **Edit digital asset** screen.
- Incorrect behavior occurs when accessing a perspective using the **Manage digital assets** service.
- Change the default value for **All file extensions** from **0** to **""**.
- A blank screen briefly appears when attaching a large number of assets.
- An asset cannot be shared via email on the **Digital Asset Manager - Editor** screen on a Relational model.

Release Notes 1.8.1

Release Date: December 10, 2019

Updated behavior

The add-on no longer refreshes data model schemas by retrieving a list of all registered models in the repository.

Release Notes 1.8.0

Release Date: November 8, 2019

New features and updates

The following sections highlight the new features and updates for this release:

- [Features and enhancements](#)
- [API updates](#)

Features and enhancements

- You now have the option of enabling encryption upon Drive creation. This option encrypts all assets in a Drive so they can only be accessed by a user logged in to EBX®.
- When uploading multiple files, asset thumbnails now display immediately after upload of that asset is complete.
- A Drive can now be configured to access an externally managed storage location. For example, assets might be stored in the cloud on Google Drive or AWS. Alternatively, you might already use a third-party tool to manage digital assets but, you want to enable data model access to these assets. Note that API implementation is required for these types of use cases.
- To improve user experience in certain deployment environments, Spring configuration has been moved from hybrid to pure Java.
- It is no longer mandatory for Digital Asset Components to have associated tag clouds.
- A result page now displays after running the **Delete all assets in Drive** service.
- By default all file types are now supported and enabled for upload by the add-on. However, you can use two new properties **Restrict file upload** and **Blacklisted extensions** to whitelist and

blacklist file extensions, respectively. See, [Whitelisting and blacklisting file formats](#) for more details.

- SVG files are now supported.

API updates

Using the add-on's API you can now access externally managed storage locations. These locations can include assets managed by third-party tools. In addition to linking to and displaying these assets in EBX® data model fields, you can:

- Search for and filter assets.
- Enable upload and deletion of assets.
- Attach and detach externally managed assets to EBX® data model fields.
- Display externally managed tags.

Known limitations

This release contains the following limitations:

- When accessing assets in an external Drive, error messages may display when selecting all assets. This can be the result of access limitations put in place by the third-party tool.
- Without width and height measurements, the thumbnail and content of an SVG asset are not properly displayed.

Bug fixes

This release contains the following bug fixes:

- The Vietnamese title of a downloaded file is wrong.
- A thumbnail label that contains HTML elements is not correctly displayed in the **Edit digital asset** screen.
- On the list view mode the thumbnail of an asset overlaps the outer border of the media type field.
- **Label and description** value is not saved after being modified in the **Digital asset** table.
- An user-unfriendly error page displays in the **Editor** and **Manage digital assets** screens when users attempt to download a non-existent asset.
- The error icon displays incorrectly when using quick upload.

- The **Select all** button does not work on the **Editor** screen after assets have been detached.
- The loading icon is not aligned with other thumbnails in the row when quickly uploading an asset.
- Assets cannot be displayed on the field when they are attached from the **Editor** screen and the view mode has been changed in the D.A.C.
- Incorrect behavior is presented when user selects the **Apply** checkbox on the search pane.
- A redundant header appears on the upload modal dialog from the **Icon** field on **File extension** record.

Release Notes 1.7.0

Release Date: June 20, 2019

New features and updates

The following sections highlight the new features and updates for this release:

- Features and enhancements
- API updates

Features and enhancements

- The **Manage digital assets** service can now be launched from EBX® perspectives. The service can allow users control over assets linked to one or more Drives.
- When choosing a new asset as the current version, the new asset's file name can be automatically populated to the **Editor** using the new **Update label** option.
- Add-on performance has been improved when a schema refresh is required.
- The Jackson library has been upgraded due to a security issue.
- The PhotoSwipe library has been removed from the add-on.
- When playing asset videos from within the add-on, the video is now streamed instead of downloaded.
- An asset thumbnail can now be displayed in EBX® tables. See [Enabling thumbnail display in tables](#) for more information. The following image shows an example of this feature:

Location

+ Actions ▾

	id ^	Country Code		State		City	Destination Type	Views of Area
☐	1	us		CO		Lake City	Mountains	
☐	2	us		CO		Silverton	Mountain	

API updates

The API now includes the following; please refer to the *Java API* documentation for additional information and samples:

- The API now permits assets managed by third-party tools to be linked to data model fields.
- A custom filter can now be implemented that determines the assets displayed when users enter the **Editor**.
- Sample code has been added to demonstrate implementing cloud storage for assets.
- The Digital Asset `UIBean` has been replaced by `CustomWidget`.

Bug fixes

This release contains the following bug fixes:

- Text overlap occurs in the PDF version.
- Grant permission while calling DAM API in Script tasks.
- The loading icon persists when previewing a large video (more than 164MB).
- A blank page is shown when users access document files on UI Bean when the drive has been deleted by another user.
- An error is raised when accessing assets on UI Bean if the D.A.C. has been deleted by another user.
- A blank space appears on the 'Edit digital asset' and 'Import a new version' screens.

- The error message must be unified when user accesses an asset on DAM UI Bean in case the asset or the D.A.C. is deleted.
- An unreasonable message is given when user downloads assets from different screen.
- The scroll bar does not move down to the newest point on the upload modal screen.
- The search page box does not work when previewing document assets in Internet Explorer.
- The error message must be unified when a user accesses an asset on the **Editor** if the asset or the D.A.C. is deleted.
- Large videos (more than 164MB) cannot be downloaded.
- Error log at runtime occurs when deploy an add-on using UI Framework.
- A tag cannot be created when a user re-selects an existing tag on upload modal screen.
- A `NullPointerException` occurs while registering `DriveManager`.

Release Notes 1.6.0

Release Date: March 25, 2019

New features and updates

The following sections highlight the new features and updates for this release:

- [General updates](#)
- [Updates to the UI](#)


General updates

This release contains the following new features and updates:

- The add-on now supports TIBCO EBX® restriction policy functionality for user permissions.
- A programmatic filter can now be used to filter assets displayed in the editor.
- The `baseUrl` parameter has been removed from the `DigitalAsset.getURL()` method.
- A public REST service has been provided to upload an asset.
- Documented code samples have been updated.
- Support has been added to take into account the new version of the TIBCO EBX™ Information Search Add-on (2.4.0).

Updates to the UI

- The **Manage digital assets** UI has been updated.
- The following updates were made to the **Editor** UI:
 - The UI is now responsive and automatically resizes based on the window or screen size.
 - Infinite scroll has been added to the **Editor** for assets and tags.
 - As highlighted in the image below, the UI layout has also been updated:



Bug fixes

This release contains the following bug fixes:

- The title of the download pop-up is incorrect when running the **Import from a ZIP file** service.
- A JavaScript error is raised in Internet Explorer when cancelling an upload.
- No message is given when user imports a ZIP file exceeding available server space.
- The user can change the current version without having sufficient permission.
- The error icon's red border no longer displays when a user hovers their mouse over the icon.

Release Notes 1.5.1

Release Date: December 14, 2018

Featured updates

The Creative Commons license has been moved from ECI to BAS.

Bug fixes

This release contains the following bug fixes:

- The **Identify unused asset** service does not work with assets on the media type field under a group.
- The **Identify unused asset** service does not work with assets on the media type field under a table belonging to a group.

Release Notes 1.5.0

Release Date: October 26, 2018

New features and updates

This release contains the following new features and updates:

- The new **Change physical root path** service allows you to update a Drive's storage location. Once updated all add-on related assets are migrated to the new location.
- REST services for TIBCO EBX™ GO Add-on have been implemented.
- Significant updates have been included to ensure compatibility with the EBX® 5.9.0 GA release.

Bug fixes

This release contains the following bug fixes:

- The **Permanently delete digital asset** and **Delete digital asset version** services do not work on a hierarchy view.
- Lack of a border and a text overflow when a tag has long text.
- Users cannot create tags containing quotation marks on the **Upload new digital assets** dialog.

- Users are not allowed to close the **Upload** pop up while uploading assets.
- Inconsistent display of **Upload** and **Edit** buttons between a media type field using **Quick upload and attach** and the UI.
- The display of service buttons on the thumbnail of asset on the Digital Asset Manager UI Bean are inconsistent.
- An error message occurs when users click **Select all** after detaching assets including the **File not found** items.
- The upload files process does not work properly.
- The search pane's tooltip on the **Editor / Manage digital asset** screen is wrong.
- An incorrect tooltip is displayed for the **Cancel** button in the **Importing assets** screen.

Release Notes 1.4.3

Release Date: November 29, 2018

Featured updates

The Creative Commons license has been moved from ECI to BAS.

Bug fixes

This release contains the following bug fixes:

- The **Identify unused asset** service does not work with assets on the media type field under a group.
- The **Identify unused asset** service does not work with assets on the media type field under a table belonging to a group.

Release Notes 1.4.2

Release Date: September 13, 2018

Featured updates

The Digital Asset Manager Add-on has undergone updates to ensure compatibility with the EBX® 5.8.1 fix M release.

Release Notes 1.4.1

Release Date: June 22, 2018

Bug fixes

Files cannot be uploaded due to a conflict with the jQuery library.

Release Notes 1.4.0

Release Date: May 2, 2018

New features


The following sections describe new features for the GA 1.4.0 release:

- [Previewing assets](#)
- [Importing assets in bulk](#)
- [Record filtering](#)
- [REST services](#)


Previewing assets

The add-on now includes the ability to preview additional types of assets. See [Previewing assets](#) for more detailed information. The newly supported types are:

- MP4 files: When previewing, the add-on automatically starts the video and enables basic playback control.



- Document files: When previewing PDF, DOC, DOCX, PPT, or PPTX assets you can use standard document viewer features, such as zoom, navigation, and search.



Importing assets in bulk

Administrators now have the option to perform a bulk upload of assets by importing a ZIP file. After import, the **Result** page's **Actions** menu enables:


- Download of a log file if the import failed.
- Comparison of two or more imported assets.
- Export of the report in CSV or XML format if the import was successful.

See [Performing a bulk upload](#) for more information.


Record filtering

The add-on now provides the ability to filter the following types of records:

- Asset records that are not attached to a field. The new **Identify unused assets** service locates and displays all assets not attached to a field. From this view you can compare assets and export reports in CSV and XML formats. For more information, see [Finding and removing unused assets](#).



- Table records with no attached assets. The EBX® filter now contains the **Digital Asset Manager Add-on search** filter. The filter can be used to show/hide records that have attached assets. For more information, see [Configuring asset filters](#).



REST services

REST services are now available to:

- Get all digital assets from a Drive.
- Attach and detach assets from a field.

See [REST service operations](#) for examples.

Known limitations

This release contains the following limitations:

- A JavaScript error is raised in Internet Explorer when canceling an upload.
- The progress bar does not work properly when importing from a ZIP file.
- Document previews cannot display Vietnamese text.

- The video seek bar does not work properly when a user previews MP4 files in Google Chrome.

Bug fixes

This release contains the following bug fixes:


- Users can still view assets in the **Editor** after another user has deactivated the asset.
- Users can view other's assets even without sufficient permission in the D.A.C. or Drive.
- An error occurs on the loading page when clicking the 'Reset filter' button on the **Editor** screen.

Release Note 1.3.0

Release Date: December 15, 2017

Overview of features and enhancements

- [Usability improvements](#)
- A new **Information** icon is available on asset thumbnails. Clicking this icon opens the **Edit digital asset** screen where you can view detailed information about the asset, its versions, and its metadata.



- You now have the option of determining whether quick action icons always display on assets, or only when users mouse over the asset.
- When viewing asset versions, you can now download individual versions for comparison.

Digital Asset Manager - Edit digital asset

Information | **Version management** | Metadata

New version ▾ ← Use the 'New version' group to upload a new version of this asset.

File * No file selected.
The file extension must be the same as the digital asset's extension.

Version name

Comment

Current version ☐

Digital asset versions

	Physical name	Version name	Comment	Current version	
	Small Falls - Horizontal - BW.jpg	Black n White		☐	  
	Small Falls - Horizontal.jpg			☒	  

Specify the current version, edit the 'Version name' and 'Comment', download a copy, or remove a version.


- New REST services are available that allow you to:
 - Retrieve an asset's URL.
 - Get all mediaType fields registered in Digital Asset Manager Add-on.
 - Get information about assets attached to a mediaType field.

Usability improvements

A large portion of the asset management process involves getting your assets into the manager. With this in mind, the latest version of the Digital Asset Manager Add-on provides the following usability improvements focused on helping you during the upload process (see [Uploading and attaching assets](#) for more information):

- Instead of bringing in assets individually, you can now upload and attach more than one asset at a time.
- A new quick-upload mode allows users to bypass pop-up dialogs and directly upload and attach assets. This mode integrates well with workflows.
- In addition to browsing to select files, drag-n-drop functionality is now included in the upload screen.
- Duplicate asset management during upload has been improved. The upload screen now indicates which assets are duplicate and you can choose whether to keep, or remove these assets during upload.
- When browsing for files to select during upload, the add-on applies a filter and only displays those extensions supported by the current D.A.C. configuration.

The following image highlights some of the aforementioned features:



Bug fixes

- The 'Tag' text box disappears in the 'Manage digital assets' screen after removing tag on an asset.
- The 'Drive' field is null and Tags are displayed after changing value of 'Drive' in the D.A.C.
- An error occurs on the Digital Asset Manager UI Bean and an exception is thrown in the log when users use an uncompleted list view.
- An error occurs and an exception is thrown in the log when running 'Attach' or 'Detach' with an uncompleted list view.
- A record cannot be created by using 'Duplicate record' on 'Drive' table in the 'TIBCO EBX™ Digital Asset Manager Add-on' dataset.
- An error occurs when the media type field is in a group with multiple elements.
- A newly uploaded asset is attached into the first occurrence in spite of being uploaded from another media type field.
- Overlap occurs in the 'Editor' screen on IE8.
- Users can create an image configuration even when the mandatory fields of 'Max width' and 'Max height' are empty.

- The 'Bin' icon is displayed without thumbnail on the Digital Asset Manager UI bean after detaching the asset on IE8.
- A user can still open the Editor screen without sufficient permission.
- An unsupported file can be attached to the 'File attachments' pane on the Editor screen.
- An exception is thrown in the log when inputting a value into the 'Metadata' table without choosing 'Metadata nature'.

Release Note 1.2.2

Release Date: November 7, 2017

New features

- You can now download assets contained in read-only records.
- It is now possible to upload a new asset version from the list view.
- A new REST service is available to retrieve a digital asset's URL.

Release Note 1.2.1

Release Date: October 16, 2017

New features

- Take into account the new version of TIBCO EBX™ Information Search Add-on (2.0.0).

Release Note 1.2.0

Release Date: September 6, 2017

New features

UI updates and improvements

- The Editor layout has been improved.
- Assets can be displayed in fields using a combination of settings that include using thumbnails, or icons and using a list, or tiled mosaic view.

- Display of asset thumbnails has been improved and also retains an image's original aspect ratio.

Functionality improvements

- User permissions have been expanded and can now be set at the Drive and D.A.C. levels.
- In the Editor, assets can be selected to shown an expanded view. Several options for downloading, editing, and sharing are available from the expanded view.
- Search, sort, and filter options available in the Editor have been updated.
- An asset's label description, version name and comments, and tags can be modified during upload.
- The following actions can be performed when mousing over an asset thumbnail: detach, download, or import of a new version.
- Tag domains have been replaced with tag clouds. Tag clouds can be used to organize tags and display them in the Editor.
- Duplicate assets can now be uploaded.
- Uploaded assets are saved in sub-folders so that the limitations of certain file systems don't prevent the upload of additional assets.

Bug fixes

- Users cannot run the Restore service when they do not have delete permission on a Drive contained in the backup file.
- There is a redundant 'Upload new digital asset' dialog when users upload an asset.
- There is an error when clicking a thumbnail that has been accidentally deleted in the file system.
- An asset's label displays incorrectly when users input HTML characters.
- A 403 page error occurs when users click on the download button from Digital Asset Manager UI Bean.
- Multiple errors occur when users input HTML characters into Domain and Tag domain.
- The tooltip of an asset is not updated after running the Refresh service.
- An error occurs after clicking on the 'Create a record' button in the 'History' table.
- The label and textbox of the 'Domain' field are not positioned correctly.
- An unknown record is automatically created in the 'Digital Asset Type' table.

Release Note 1.1.1

Release Date: August 16, 2017

Bug fixes

- A 'Drive type' that connects to cloud storage cannot be created.

Release Note 1.1.0

Release Date: April 18, 2017

New features

- A new public API is available to create, update, and delete digital assets and versions. It also allows connection to additional types of drives.

Bug fixes

- The system returns incorrect results when filtering label and domain.
- The 'Last update date' is not updated after users update domain and tag of an asset.
- Unauthorized access to resources is possible.

Warnings

- Customers are strongly advised to upgrade to the latest version which patches the security issue.

Release Note 1.0.2 fix 001

Release Date: April 18, 2017

Bug fixes

- Unauthorized access to resources is possible.

Warnings

- Customers are strongly advised to upgrade to the latest version which patches the security issue.

Release Note 1.0.3

Release Date: April 3, 2017

Bug fixes

- Even when users deactivate a digital asset, it still appears in the 'Digital asset list' pane, 'Attached' pane, and 'Media' field.
- The wrong current version of digital asset is downloaded.
- There is an error when previewing the digital asset when the file has been accidentally deleted in the file system.
- The digital assets cannot be loaded when the 'Digital asset type' option is set to 'image'.
- After modifying business version or comment, the system uploads the previously selected file again.
- Domain for a digital asset cannot be created when the 'Domain' field contains special characters.
- An unexpected error occurs in version management tab when displaying a digital asset without setting the current version.
- An unexpected error occurs when a digital asset has no label.
- Digital asset is not deleted after users click the 'Cancel upload' button.
- An unexpected error occurs when users modify `ebx.locales.available=en` in `ebx.properties`.

Release Note 1.0.2

Release Date: January 23, 2017

New features

- When specifying a Drive's storage location using the 'Physical root path' property it is now possible to use a relative path.

Bug fixes

- Abnormal behavior is recorded when importing an EBX® file.

Release Note 1.0.1

Release Date: October 28, 2016

New features

- Images that use the CMYK color space can be managed with the Digital Asset Manager Add-on.

Release Note 1.0.0

Release Date: October 12, 2016

New features

- A 'Media-type' field can be added to a data model to enable digital asset management.
- Assets can be uploaded using the add-on's services supplied at the administrative, dataset and field levels.
- An editor is available that allows you to perform the following actions on digital assets: upload, select, deselect, search, filter, edit, preview, download, share, deactivate and delete.
- Several custom services are available that allow you to perform asset management-specific actions in. The services are covered in more detail in the main documentation.
- It is possible to create a backup of, and restore the Digital Asset Manager Add-on's configuration settings and assets.